

4K professional display

Portrait orientation

22.3 mm thick free-standing chassis

Plug and Play



Ultra-slim and sleek, the freestanding Vision DSD-55 is the ideal digital signage display for powerful visual messaging. Designed with a scratch-resistant glass front panel for added durability, it offers unrivaled visibility regardless of dust or ambient light. The 4K panel is equipped with dual 10W stereo speakers, 178° wide-angle display, and 350 nits brightness, projecting clear, vibrant images and videos to captivate the audience. The DSD-55 enables seamless multimedia playback of choice with locking internal storage for media player or mini PC. It comes with 2x HDMI input, 1x DP input and 1 USB input.

Easy Setup

This product has been given the trademark Vision treatment to make assembly and operation as easy as possible. If you can install a TV you can set this product up.

Razor-Thin

Just 22.3 mm thick and featuring a display that extends close to the edges, this kiosk represents the forefront of design. Gently rounded edges enhance the quality of the fit and finish.

Professional display

This high-grade display is built to last beyond 50,000 hours. It lacks a built-in media player or internal operating system, so you will need to connect a PC or media player via the HDMI port.

Built-in Audio

Integrated speakers featuring a 2 x 5W amplifier at 8 ohms.

Lockable Storage

To access the input ports and install a media player, open the back door.

Remote Control

The package includes a full-featured IR remote.

SPECIFICATIONS

DIMENSIONS

1960 x 764 x 450 mm / 77" x 30" x 18" tall x wide x deep

CARTON DIMENSIONS

1950 x 875 x 225 mm / 77" x 34" x 9" length x height x width

PRODUCT WEIGHT

54 kg / 119 lb

PACKAGED WEIGHT

58 kg / 128 lb

COLOUR

Black

INPUTS

2 x HDMI 1 x DisplayPort 1 x USB (for upgrades)

AUDIO OUTPUT

Integrated 2 x 5 Watts RMS @ 8 OHMS amplifier with speakers 1 x 3.5mm Minijack Audio line-level output

OPERATING TEMPERATURE

0 - 40°C / 32 - 104 °F

POWER CONSUMPTION

On: 96 W Standby: 1.4 W

ACCESSORIES INCLUDED

1 x UK IEC power cable 1.8 m long 1 x EU IEC power cable 1.8 m long Remote Control

POWER SUPPLY

110-240V 50/60 Hz

WARRANTY

1 Year - Excluded from Vision Standard Lifetime

COMPLIANCES

RoHS, WEEE, CE/EMC, CE/LVD, UKCA

DISPLAY

Industrial 55" BOE panel

FRAME RATE

50-60 Hz

NATIVE RESOLUTION

3840 x 2160 4K

ASPECT RATIO

9:16

BRIGHTNESS

350 NITS (cd/m²)

DISPLAY AREA

1210 mm x 680 mm

CONTRAST

1200:1

COLOURS

16.7M

VIEWING ANGLE

H: 178° V: 178°

LIGHT SOURCE RATING

50,000 HRS

MANUFACTURER PART NUMBER

DSD-55 [SAP: 10518479]

OPERATING HUMIDITY

10-80% RH

STORAGE TEMPERATURE

Recommended: 5°C - 40°C / 41 - 104 °F Max: -10°C - 60°C / 14 - 140 °F