

55" 4K professional display

Portrait orientation

22.3 mm thick free-standing chassis

Plug and Play



Make an unforgettable impression in retail or hospitality settings with ultra-slim 4K signage displays. A modern razor-thin display, this 55" kiosk provides stunning resolution perfect for captivating and engaging your audience. Elevate your message with the ultimate visual innovation.

The whole front face is glass, completing the full integration of the display and chassis, distinct from the typical bulky AV totems.

Easy Setup

This product has been given the trademark Vision treatment to make assembly and operation as easy as possible. If you can install a TV you can set this product up.

Razor-Thin

Just 22.3 mm thick and featuring a display that extends close to the edges, this kiosk represents the forefront of design. Gently rounded edges enhance the quality of the fit and finish.

Professional display

This high-grade display is built to last beyond 50,000 hours. It lacks a built-in media player or internal operating system, so you will need to connect a PC or media player via the HDMI port.

Built-in Audio

Integrated speakers featuring a 2 x 5W amplifier at 8 ohms.

Lockable Storage

To access the input ports and install a media player, open the back door.

Remote Control

The package includes a full-featured IR remote.

SPECIFICATIONS

DIMENSIONS

1960 x 764 x 450 mm / 77" x 30" x 18" tall x wide x deep

CARTON DIMENSIONS

1950 x 875 x 225 mm / 77" x 34" x 9" length x height x width

PRODUCT WEIGHT

54 kg / 119 lb

PACKAGED WEIGHT

58 kg / 128 lb

COLOUR

Black

INPUTS

2 x HDMI 1 x DisplayPort 1 x USB (for upgrades)

AUDIO OUTPUT

Integrated 2 x 5 Watts RMS @ 8 OHMS amplifier with speakers 1 x 3.5mm Minijack Audio line-level output

OPERATING TEMPERATURE

0 - 40°C / 32 - 104 °F

POWER CONSUMPTION

On: 96 W Standby: 1.4 W

ACCESSORIES INCLUDED

1 x UK IEC power cable 1.8 m long 1 x EU IEC power cable 1.8 m long Remote Control

POWER SUPPLY

110-240V 50/60 Hz

WARRANTY

Lifetime return-to-base

COMPLIANCES

RoHS, WEEE, CE/EMC, CE/LVD, UKCA

DISPLAY

Industrial 55" BOE panel

FRAME RATE

50-60 Hz

NATIVE RESOLUTION

3840 x 2160 4K

ASPECT RATIO

9:16

BRIGHTNESS

350 cd/m2

DISPLAY AREA

1210 mm x 680 mm

CONTRAST

1200:1

COLOURS

16.7M

VIEWING ANGLE

H: 178° V: 178°

LIGHT SOURCE RATING

50,000 HRS

MANUFACTURER PART NUMBER

DSD-55 [SAP: 10518479]

OPERATING HUMIDITY

10-80% RH

STORAGE TEMPERATURE

Recommended: 5°C - 40°C / 41 - 104 °F Max: -10°C - 60°C / 14 - 140 °F