



30w Active Soundbar

SB-800P EU SAP: 3872395 US SAP: 12928301

vav.link/sb-800p

Built-in 2 x 15 watt (RMS) amplifier
Line-level inputs or speaker-level inputs
Wall brackets and flat-panel brackets included

Vision's SB-800P Soundbar is a simple way to add quality audio to professional flat-panel screens which do not have speakers integrated. The attractive chassis enhances any audio-visual installation in meeting rooms, boardrooms, and conference rooms.



Mobile Audio

If users need to be able to move their interactive flat panel screen between rooms Vision's soundbar is the perfect choice. The soundbar can be hung under the flat panel, attaching to the flat panel floor mount at the same points the flat panel uses.

4-Way

Two 3.5" woofers are complemented by two tweeters. A crossover circuit splits the frequency spectrum across four drivers to maximise efficiency.

Volume Control

The volume dial is positioned underneath the loudspeaker. Turning anti-clockwise turns power off. Note: no remote control is included.

Wall Bracket

If the flat-panel is wall mounted then a wall bracket is included which fixes the soundbar close to the wall.

Hanging Brackets

A set of 700 mm (27.6") brackets is also included which hang the soundbar under the flat panel.

Speaker-Level Input

As well as being able to connect any line-level device to the SB-800P – like your phone – you can also opt to bypass the internal amplifier and use the soundbar as passive speakers. Some flat panels have an amplifier inside, so this approach allows you to use the flat-panel remote to adjust volume.

ABS Chassis

Heavy-weight plastic material is used for the chassis, allowing a beautiful curved chassis and a rigid acoustic chamber for low-distortion sound.

Two Summed Line-level Inputs

The input panel offers minijack and 2-phono (RCA) line-level inputs which are combined at the input stage meaning there is no input selection switch. When both inputs are used it is especially important that all source and display devices in the system are powered from the same mains power source, otherwise earth hums will occur.

VISION

MANUAL

Dims

EN PDF 786.04 KB

files.visionaudiovisual.com/products/SB-800P/manuals/SB-800P_dims.pdf

Manual

EN PDF 457.25 KB

files.visionaudiovisual.com/products/SB-800P/manuals/SB-800P_manual_en.pdf

CAD

CAD

ZIP 1.56 MB

<files.visionaudiovisual.com/products/SB-800P/cad/SB-800P.zip>

CAD

VND.DWG 1.66 MB

<files.visionaudiovisual.com/products/SB-800P/manuals/SB-800P.dwg>

IMAGE

Ont

PNG 320.80 KB

files.visionaudiovisual.com/images/products/SB-800P/SB-800P_front.png

Ont angle

PNG 440.27 KB

files.visionaudiovisual.com/images/products/SB-800P/SB-800P_front_angle.png

Inputs

PNG 271.46 KB

files.visionaudiovisual.com/images/products/SB-800P/SB-800P_inputs.png

Rear angle

PNG 124.96 KB

files.visionaudiovisual.com/images/products/SB-800P/SB-800P_rear_angle.png

Under

PNG 459.67 KB

files.visionaudiovisual.com/images/products/SB-800P/SB-800P_under.png

Product Images

ZIP 1.46 MB

<files.visionaudiovisual.com/products/SB-800P/images/SB-800P.zip>

Front

PNG 320.80 KB

files.visionaudiovisual.com/products/SB-800P/images/SB-800P_front.png

Inputs

PNG 271.46 KB

files.visionaudiovisual.com/products/SB-800P/images/SB-800P_inputs.png

Rear angle

PNG 124.96 KB

files.visionaudiovisual.com/products/SB-800P/images/SB-800P_rear_angle.png

Front angle

PNG 440.27 KB

files.visionaudiovisual.com/products/SB-800P/images/SB-800P_front_angle.png

Under

PNG 459.67 KB

files.visionaudiovisual.com/products/SB-800P/images/SB-800P_under.png

SPECIFICATIONS

PRODUCT DIMENSIONS

756 x 75 x 99mm / 29.8" x 2.9" x 3.9" (width x depth x height)

PACKAGED DIMENSIONS

870 x 92 x 135 mm / 34" x 3.6" x 5.3"

PRODUCT WEIGHT

2 kg / 4.4 lb

PACKAGED WEIGHT

2.7 kg / 5.9 lb

CONSTRUCTION MATERIAL

ABS Plastic

COLOUR

Black

AMPLIFIER OUTPUT

2 x 15w watts (RMS)

WOOFER

2 x 3.5"

TWEETER

2 x 0.5"

INPUT 1

Minijack (3.5mm)

INPUT 2

2-Phono (RCA) (inputs are summed)

SPEAKER INPUT (FROM FLAT PANEL IF IT HAS INTERNAL AMPLIFIER)

Removable Phoenix type

OUTPUT IMPEDANCE

8 ohms

SENSITIVITY

88dB (1w/1m)

FREQUENCY RESPONSE

120Hz-20kHz

ACCESSORIES INCLUDED

1 x Wall bracket 2 x 700mm mounting strips – to hang soundbar beneath flat panel Note: no input cables are included

POWER SUPPLY

100-240v 50/60Hz AC External Power Supply – 18 volt / 1 amp

TRANSFORMER INTEGRATED INTO PLUG

INCLUDES INTERCHANGEABLE PLUGS

UK/EU/US/AU

DC TAIL LENGTH

4m

TRANSFORMER DIMENSIONS

75 x 38 x 50mm / 3" x 1.5" x 2" (tall x wide x deep) including prongs

WARRANTY

Lifetime return-to-base

COMPLIANCE

RoHS, WEEE, CE/EMC, FCC, IEC, RCM-POC, RCM-SDOC, REACH

ORDER PART CODE

SB-800P

SPARE POWER SUPPLY UNIT (PSU)

TC2 P18V1A [EU SAP: 3675051/ US SAP: 13445526]

