

- Built-in 2 x 27 watts (PEAK) amplifier
- Minijack input
- Bluetooth input
- Wall brackets and brackets to hang under display included
- Auto-Standby (can be disabled)
- Auto-Resume when power cycled



The Vision SB-900P soundbar is a value sound reinforcement product in a beautiful chassis. The design enhances any audio-visual installation in meeting rooms, boardrooms, and conference rooms.

Bluetooth

An easy to use Bluetooth connection takes just a moment to pair. Note: Bluetooth can't be renamed. For this feature see the SB-1800P.

Directional Projection

The sound is projected forward in a tight pattern to help audio conference phones filter out echoes.

High Clarity

Very clear mid and high frequencies help it push the sound into a big room. High quality drivers ensure no tiring high frequency distortion.

Analogue Input

A stereo line-level Minijack input handles normal analogue sources.

Power Cycling

If mains power is turned off and on, the SB-900P will automatically come back on resuming the previous settings.

Auto Standby

Choose to use the standard auto standby setting to conserve power, or hold down VOL+ to disable auto-standby.

Hanging Brackets

A set of brackets are included which hang the soundbar under the flat panel. The speaker also comes with rubber feet if you need to place on a shelf, and wall-hanging lugs.

Mobile Audio

Need to move your interactive flat panel display between rooms? Vision's soundbars are the perfect choice, fixing under the display to the floorstand.

SPECIFICATIONS

PRODUCT DIMENSIONS

745 x 93 x 62 mm / 29.7" x 3.7" x 2.4" (width x depth x height)

PACKAGED DIMENSIONS

900 x 135 x 105 mm / 35.4" x 5.3" x 4.1"

PRODUCT WEIGHT

1.4 kg / 3.1 lbs

PACKAGED WEIGHT

2.0 kg / 4.4 lbs

CONSTRUCTION MATERIAL

Plastic

COLOUR

Gloss Black

AMPLIFIER OUTPUT

2 x 27 watt (PEAK) / 2 x 15 watt (RMS) at 8 ohm

DRIVERS

2

INPUT 1

Aux in (3.5mm)

INPUT SENSITIVITY

500mV

SPEAKER IMPEDANCE

8 ohms

SENSITIVITY

88dB (1w/1m)

FREQUENCY RESPONSE

90Hz-20kHz

POWER CONSUMPTION

30w (<0.5W standby)

BLUETOOTH

V4.2

MAXIMUM POWER TRANSMITTED

<5 dBm

FREQUENCY BANDS

2402-2480 MHz

POWER INPUT

DC 20V/3A

ACCESSORIES INCLUDED

2 x L shaped universal mounting strips – to hang soundbar beneath flat panel 1 x 20 cm (8") Minijack Y cable - sums two inputs into one, black 4 x 1.5 m (4.9ft) Figure-8 power cable (right-angle plug: UK/EU/US, normal plug: AU), Black

POWER SUPPLY

100-240v 50/60Hz AC Internal Power Supply

WARRANTY

Lifetime return-to-base

COMPLIANCE

RoHS, WEEE, CE/RED, FCC, IC, RCM-POC, RCM-SDOC, RCM-NERS

SPARE POWER SUPPLY UNIT (PSU)

TC P18V3A [SAP: 4753914]