

5.25" Woofer 50w loudspeakers

Wall brackets included with 60° range of tilt adjustment

White, sold in pairs



Vision's SP-1800 professional wall mounted loudspeakers are super-easy to install, look beautiful, and produce rich and powerful sound.

They are 240mm tall and use a 5.25 inch woofer – the most popular size for classroom, meeting room, and boardroom applications.

### Three-Way

These loudspeakers use three drivers; a woofer, a squawker, and a tweeter. Asking a driver to produce a wide range of frequencies is always a compromise, so dividing the sonic range into three means each driver has a narrower range of frequencies to produce, resulting in less distortion and clearer sound.

### Bass Reflex

A bass reflex port allows greater excursion of the woofer, allowing the woofer to produce lower frequencies, and the phase-delayed movement of air from behind the woofer to the front reinforces the bass even more.

### Rugged Grille

A metal grille protects the drivers from physical interference.

### Tough Finish

Constructed with tough ABS plastic, the finish withstands the rigors of the professional use.

### Pro AV Applications

In small to medium presentation environments a wide dispersion is generally more important than microphone feedback management, so no horns are used.

### Horizontal C bracket

The adjustable brackets allow the installer to easily angle up 30° or down 30°. Or leave the brackets off and use as shelf speakers.

### Note

These are passive loudspeakers – there is no amplifier built in – so they need to be used with an external amplifier.

## SPECIFICATIONS

**PRODUCT DIMENSIONS**

244 x 180 x 174 mm (tall x wide x deep for each speaker)

**PACKAGED DIMENSIONS**

465 x 205 x 270 mm

**PRODUCT WEIGHT**

4.2 kg (per pair)

**PACKAGED WEIGHT**

4.67 kg (per pair)

**CONSTRUCTION MATERIAL**

ABS

**COLOUR**

White

**POWER HANDLING**

50 watts (RMS)

**WOOFER**

5.25"

**SQUAWKER**

1"

**TWEETER**

0.5"

**INPUT TERMINALS**

Binding post

**OUTPUT IMPEDANCE**

8 ohms

**SENSITIVITY**

89dB (1w/1m)

**FREQUENCY RESPONSE**

80Hz-20kHz

**ACCESSORIES INCLUDED**

2 x Wall brackets

**WARRANTY**

Lifetime return-to-base

**COMPLIANCE**

RoHS, WEEE, CE/ EMC, FCC, RCM-POC, RCM-SDOC, REACH, UKCA

