

Built-in 2 x 30 watts amplifier
Line-level input via 2-phono (RCA)
Bluetooth 5.0 (can be disabled)
RS-232 Control
Tone control (via RS-232)



Vision's professional 5.25" powered bookshelf speakers are purpose-built for any audio-visual presentation environments such as classrooms and meeting rooms, or bars and restaurants. They are simple to install and control. Perfect for meeting spaces or small rental applications.

Serial Control

RS-232 control allows this audio system to be controlled by a control system like Vision's own Techconnect Control. Tone and volume can be adjusted or inputs selected via RS-232. *Note: this product does not have a remote control.*

Auto Standby

Auto-standby is on by default. It can be disabled via RS-232.

Bass Reflex

A bass reflex port allows greater excursion of the woofer, allowing the woofer to produce lower frequencies, and the phase-delayed movement of air from behind the woofer to the front reinforces the bass even more.

5.25" Woofer

These loudspeakers use a 5.25 inch woofer – the most popular size for classroom, meeting room, and boardroom applications. They are complemented with a 0.5" inch Mylar dome tweeter.

Horizontal C bracket

The adjustable brackets allow the installer to easily angle side to side, or up and down. Or leave the brackets off and use as shelf speakers.

Rugged Grille

Attractive and robust, the thick metal grille protects the drivers from physical interference.

Memory

When power is connected the SP-1900P automatically comes on and remembers the previous volume setting. Restoring power brings the loudspeakers back to life automatically.

Stereo Input

The 2-Phono (RCA) input makes it quick and easy to get up and running.

Bluetooth

Connect from your phone or tablet without missing a beat. By default the speakers auto-switch from the line-level input when Bluetooth is paired.

A button on the rear turns BT off if you don't need it

The PIN and Bluetooth name cannot be changed

The speakers have only one Bluetooth memory slot and will automatically connect to the most recent device. To unpair an unwanted device manually wait until that device is out of range then pair a new device. They can only pair to one device at a time.

PRODUCT DIMENSIONS

245 x 183 x 164 (tall x deep x wide for each cabinet)

PACKAGED DIMENSIONS

395 x 235 x 275 mm

PRODUCT WEIGHT

Master: 2.7 kg Slave: 2.5 kg

PACKAGED WEIGHT

5.5 kg

CONSTRUCTION MATERIAL

PP

COLOUR

White

AMPLIFIER OUTPUT

Low Impedance Dynamic Power: 2 x 30 watt at 8 ohms Low Impedance RMS Power: 2 x 15 watt at 8 ohm

LOUDSPEAKER SYSTEM

2-way

WOOFER

5.25" Polypropylene Cone

TWEETER

0.5" Mylar Dome

MOUNTING SYSTEM

C-bracket

INPUTS

Stereo 2-Phono (RCA) Bluetooth

SPEAKER OUTPUT

Removable Phoenix type

BLUETOOTH VERSION

5.0

BLUETOOTH RANGE

10 m

NOMINAL IMPEDANCE

8 ohms

SENSITIVITY

86 dB (1w/1m)

FREQUENCY RESPONSE

45 Hz-20 kHz

POWER SUPPLY

100-240v 50/60Hz AC Internal Power Supply

CONTROL INTERFACE

RS-232 Serial

TOTAL HARMONIC DISTORTION (THD)

1%

ACCESSORIES INCLUDED

2 x Wall brackets 1 x Speaker Cable 5m 1 x Euro Figure-8 Power cable 1.8 m long 1 x UK Figure-8 Power cable 1.8 m long 1 x AU Figure-8 Power cable 1.8 m long 1 x US Figure-8 Power cable 1.8 m long (removed after Sep 23) Note: no input cables included

WARRANTY

Lifetime return-to-base

COMPLIANCE

RoHS, CE/EMC, FCC, RCM, RCM/TVC, RCM-SDOC, REACH, UKCA

