



Braided HDMI to VGA Adaptor

TC-HDMIVGA/HQ EU SAP: 4979150 US SAP: 13557663

vav.link/tc-hdmivga-hq

Plugs into HDMI port on a laptop. Converts digital HDMI signal into analogue VGA signal. Ideal when you are presenting in an older presentation environment which only has VGA cable between the lectern and projector.



Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.



VISION

IMAGE

Product Images

ZIP 933.05 KB

<files.visionaudiovisual.com/products/TC-HDMIVGA/images/TC-HDMIVGA.zip>

Product Images

ZIP 1.88 MB

<files.visionaudiovisual.com/products/TC-HDMIVGA-HQ/images/TC-HDMIVGA-HQ.zip>

1 2

PNG 424.99 KB

files.visionaudiovisual.com/products/TC-HDMIVGA-HQ/images/TC-HDMIVGA-HQ_1-2.png

2 1

PNG 919.79 KB

files.visionaudiovisual.com/products/TC-HDMIVGA-HQ/images/TC-HDMIVGA-HQ_2-1.png

SPECIFICATIONS

MAXIMUM RESOLUTION

1920 x 1080 @ 60 Hz (1080p Full HD)

CABLE OUTER DIAMETER

5 mm (0.2")

VGA CHASSIS SIZE

46 x 23.4 x 16.4 mm (1.8" x 0.92" x 0.65")

HDMI PLUG SIZE

39.5 x 21.5 x 11.2 mm (1.56" x 0.85" x 0.44")

OVERALL LENGTH

230 mm (9.06")

WEIGHT

40 g (1.4 oz)

PACKAGED WEIGHT

0.07 kg (0.15 lb)

PRODUCT WEIGHT

0.04 kg (0.09 lb)

PACKAGED DIMENSION

120 mm x 120 mm x 40 mm (4.7" x 4.7" x 1.6")

COLOUR

Braided

SUPPORTS HDMI 1.4B AND HDCP 1.4