



# Professional Premium Braided Mini-DisplayPort to HDMI Adaptor

TC-MDPHDMI/HQ EU SAP: 4979312 US SAP: 13557664

[vav.link/tc-mdphdmi-hq](http://vav.link/tc-mdphdmi-hq)

Plugs into Mini-DisplayPort (also known as Thunderbolt) and has full-sized HDMI socket. Active circuit allows PCs with or without Dual-Mode DisplayPort (DP++) to connect to displays with HDMI inputs.



## Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

## Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.

**VISION**

## IMAGE

---

Product Images

**ZIP 726.29 KB**

<files.visionaudiovisual.com/products/TC-MDPHDMI4K/images/TC-MDPHDMI4K.zip>

Image 1

**PNG 387.82 KB**

[files.visionaudiovisual.com/products/TC-MDPHDMI-HQ/images/TC-MDPHDMI-HQ\\_1.png](files.visionaudiovisual.com/products/TC-MDPHDMI-HQ/images/TC-MDPHDMI-HQ_1.png)

Image 2

**PNG 714.46 KB**

[files.visionaudiovisual.com/products/TC-MDPHDMI-HQ/images/TC-MDPHDMI-HQ\\_2.png](files.visionaudiovisual.com/products/TC-MDPHDMI-HQ/images/TC-MDPHDMI-HQ_2.png)

## SPECIFICATIONS

---

### CHASSIS SIZE

60 x 21 x 13 mm (2.4" x 0.83" x 0.51")

### PACKAGED WEIGHT

0.06 kg (0.13 lb)

### PRODUCT WEIGHT

0.03 kg (0.07 lb)

### PACKAGED DIMENSION

120 mm x 120 mm x 40 mm (4.7" x 4.7" x 1.6")

### SHEATH OUTER DIAMETER

6.0 mm (0.24")

### CONDUCTOR THICKNESS

32 AWG (American Wire Gauge)

### COLOUR

Braided

### HDMI 2.0

### RESOLUTION

### PS176 CHIPSET

SUPPORTS ATI EYEFINITY™ MULTI-SCREEN DISPLAY FUNCTION

### SUPPORTS 4K @ 60HZ

up to 4096 x 2160

NOT BI-DIRECTIONAL. DOES NOT CONVERT HDMI TO DP