

# **TC-USBCHUB5P USB-C Multiport Hub**

vav.link/tc-usbchub5p TC-USBCHUB5P EU SAP: 11546437



1 x HDMI 4K at 60 Hz
1 x RJ45 Ethernet 1000 Mbps
1 x USB 3.0
1 x USB-C with 100W Power Delivery Pass-Through
1 x USB-C with 4K at 60 Hz

Address the port limitations of modern laptops with this 5-in-1 multiport KVM adapter, enabling 4K60Hz HDMI video, USB-A, Gigabit Ethernet, and 100W Power Delivery Pass-Through, all via a single USB-C connection.

If you rely on a single USB-C port, this compact travel docking station provides all the connectivity you need. It converts your USB-C laptop into fully equipped workstation.

# 30cm Cable

This USB-C mini dock has a 30 cm (12") cable, offering generous reach and removing connector strain - especially good for laptops placed on stands that raise them up.

## **Universal Compatibility**

Enjoy plug-and-play functionality across a broad range of USB-C devices including laptops, tablets, and phones. It works reliably across all major operating systems including Windows, macOS, iPadOS, iOS, Android, and Chrome OS.

# **Enterprise Deployment**

This multiport adapter is the preferred choice for professional IT integrators. It is rigorously tested to ensure enterprise-grade reliability and cross-platform compatibility, and it is built to support large-scale deployments.

# **SPECIFICATIONS**

## **ENCLOSURE DIMENSIONS**

121 x 44 x 18 mm (4.7" x 1.7" x 0.7")

# **PRODUCT WEIGHT**

85 g (0.2 lb)

# **PACKAGED WEIGHT**

kg (lb)

# PACKAGED DIMENSIONS

mm x mm x mm (" x " x ")

## **COLOUR**

Black

# **COMPLIANCE**

RoHS, CE, EMC, LVD, RCM, RCM\_SDOC, IC, FCC

## **WARRANTY**

Limited Lifetime

# **INPUT**

30 cm cable with male USB 3.2 Type-C (24 pin, Gen 1, 5Gbps)

## **PORTS**

1 x HDMI (4k at 60 Hz) 1 x USB 3.2 Type-A (Gen 1, 5Gbps) 1 x USB Type-C PD100 Fast Charge Power Delivery 100w - for power only 1 x USB Type-C Data and Video (4k at 60 Hz) 5 Gbps 1 x RJ45 Gigabit Ethernet 1000Mbps Note: the laptop's port must support "DP alt mode" to support video over USB-C

# **ENVIRONMENTAL**

Operating Temperature 0 °C to +70 °C Storage Temperature -10 °C to +55 °C Humidity 5% to 90 % RH (no condensation)

## **HARDWARE**

Displays Supported: 1 Fast-Charge USB-C Port: Yes Interface: USB 3.2 Gen 1 USB Pass-Through: Yes Bus Type: USB-C Ports: 5

## CHIPSET

TBC

# **COMPATIBILITY**

macOS - all from High Sierra (10.13) on Windows - all from 8 on Chrome OS iPadOS Android

## **POWER**

Power Source: Bus Powered Host USB-C Power Delivery: 100W Output Voltage: 5 DC Power Consumption: 12W