

Plug and Play

Supports up to 4K at 30 Hz

1:1 only



SPECIFICATIONS

ENCLOSURE DIMENSIONS

63 x 38 x 13 mm (2.5" x 1.5" x 0.5")

PRODUCT WEIGHT

0.1 kg (0.2 lb)

PACKAGED WEIGHT

0.1 kg (0.26 lb)

PACKAGED DIMENSIONS

120 mm x 120 mm x 40 mm (4.7" x 4.7" x 1.6")

COLOUR

Black/Grey

OPERATING TEMPURATURE

48 Degrees Celcius Note: it is normal to be very warm to touch

COMPLIANCE

RoHS, CE

WARRANTY

Limited Lifetime

RANGE

10 Metres (33 feet)

RX POWER SOURCE

Requires 5V with minimum 1A Most HDMI ports only output 0.5A. A USBC socket is integrated for external power. A USB-A to USBC cable is provided to draw power from a spare USB-A port on display device.

RESOLUTION

Maximum 4K 30 Hz (3840 x 2160)

CABLE SPECIFICATIONS

TX: 32 AWG, OD 5.0 mm RX: 32 AWG, OD 4.5 mm

TAIL LENGTH

150 mm (6")

WIRELESS TECHNOLOGY

WIFI5 802.11ac 5GHz PtP point-to-point

ACCESSORIES

1 x USB-A to USBC cable for Rx power 0.8 m (2.7")

TX POWER SOURCE

Requires 5V with minimum 1A It can draw power from USBC 3.1 port. A backup USBC socket is integrated if external power is needed.