



USB-A is the type of connector which plugs into your laptop. USB-B is the end that plugs into your printer.

High quality braided shield and ferrite core connector at both ends to shield against EMF and RF interference.

*10m+ models have an in-line active booster (48 mm / 1.9" long x 25 mm / 0.98" wide) integrated half way along cable.

When used with Vision's Techconnect modular faceplate, we recommend using the TC2 USB+ active booster module with all cables longer than 5m (16.4 ft).

1m (3.2ft)

TC 1MUSB EU SAP: 3265177 US SAP: 12939570

2m (6.5ft)

TC 2MUSB EU SAP: 3265178 US SAP: 12939571

3m (9.8ft)

TC2 3MUSB EU SAP: 3004700 US SAP: 12939522

5m (16.4ft)

TC2 5MUSB EU SAP: 3004951 US SAP: 12939526

10m (32.8ft)

TC2 10MUSB+ EU SAP: 3244188 US SAP: 12939463

15m (49.2ft)

TC2 15MUSB+ EU SAP: 3004953 US SAP: 12939466

SPECIFICATIONS

TC 1MUSB White USB 2.0 Cable 1m (3.2ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.04 kg (0.09 lb)

PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

TC 2MUSB White USB 2.0 Cable 2m (6.5ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.08 kg (0.18 lb)

PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

FERRITE CORES USB-A END**HIGH SPEED USB 2.0 CABLE****GOLD-PLATED CONNECTORS**

TC2 3MUSB White USB 2.0 Cable 3m (9.8ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.12 kg (0.26 lb)

PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

COLOR

White

HIGH SPEED USB 2.0 CABLE**BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

TC2 5MUSB White USB 2.0 Cable 5m (16.4ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

v> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.22 kg (0.49 lb)

PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

HIGH SPEED USB 2.0 CABLE**BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

TC2 10MUSB+ White USB 2.0 Cable 10m (32.8ft) with active booster

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.35 kg (0.77 lb)

PACKAGED DIMENSION

180 x 170 x 70 mm (7.1" x 6.7" x 2.8")

HIGH SPEED USB 2.0 CABLE**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS**

TC2 15MUSB+ White USB 2.0 Cable 15m (49.2ft) with active booster

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.50 kg (1.1 lb)

PACKAGED DIMENSION

180 x 170 x 70 mm (7.1" x 6.7" x 2.8")

HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS