



### 0.5m (1.6ft)

TC 0.5MCAT6/BL EU SAP: 4911589 US SAP: 13557676

### 10m (32.8ft)

TC 10MCAT6/BL EU SAP: 4911594 US SAP: 13557614

### 1m (3.2ft)

TC 1MCAT6/BL EU SAP: 4911590 US SAP: 13557677

### 2m (6.5ft)

TC 2MCAT6/BL EU SAP: 4911591 US SAP: 13557678

### 3m (9.8ft)

TC 3MCAT6/BL EU SAP: 4911592 US SAP: 13557612

### 5m (16.4ft)

TC 5MCAT6/BL EU SAP: 4911593 US SAP: 13557613

## SPECIFICATIONS

### TC 0.5MCAT6/BL Black CAT6 Cable 0.5m (1.6ft)

#### INSULATION

HDPE, diameter: 0.97 mm (0.04")

#### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

#### CONDUCTOR THICKNESS

24AWG (7/0.2)

#### BANDWIDTH

250MHz

#### IMPEDANCE ( $\Omega$ )

100 $\pm$ 15

#### DELAY SKEW @ 20°C(NS/100M)

$\leq$ 45

#### PRODUCT WEIGHT

0.02 kg (0.04 lb)

#### PACKAGED WEIGHT

0.04 kg (0.09 lb)

#### PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

#### COLOUR

Black

#### WARRANTY

Lifetime return-to-base

#### U/UTP (UNSCREENED)

#### STRANDED BARE COPPER CONDUCTORS

#### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 10MCAT6/BL Black CAT6 Cable 10m (32.8ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PRODUCT WEIGHT

0.44 kg (0.97 lb)

### PACKAGED WEIGHT

0.46 kg (1.01 lb)

### PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

### COLOUR

Black

### WARRANTY

Lifetime return-to-base

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 1MCAT6/BL Black CAT6 Cable 1m (3.2ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PRODUCT WEIGHT

0.04 kg (0.09 lb)

### PACKAGED WEIGHT

0.06 kg (0.13 lb)

### PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

### COLOUR

Black

### WARRANTY

Lifetime return-to-base

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 2MCAT6/BL Black CAT6 Cable 2m (6.5ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PRODUCT WEIGHT

0.09 kg (0.2 lb)

### PACKAGED WEIGHT

0.10 kg (0.22 lb)

### PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

### COLOUR

Black

### WARRANTY

Lifetime return-to-base

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 3MCAT6/BL Black CAT6 Cable 3m (9.8ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PRODUCT WEIGHT

0.13 kg (0.29 lb)

### PACKAGED WEIGHT

0.15 kg (0.33 lb)

### PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

### COLOUR

Black

### WARRANTY

Lifetime return-to-base

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 5MCAT6/BL Black CAT6 Cable 5m (16.4ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PRODUCT WEIGHT

0.22 kg (0.49 lb)

### PACKAGED WEIGHT

0.23 kg (0.5 lb)

### PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

### COLOUR

Black

### WARRANTY

Lifetime return-to-base

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS