



### 0.5m (1.6ft)

TC 0.5MCAT6 EU SAP: 3265140 US SAP: 12939555

### 1m (3.2ft)

TC 1MCAT6 EU SAP: 3265141 US SAP: 12939580

### 2m (6.5ft)

TC 2MCAT6 EU SAP: 3265142 US SAP: 12939581

### 3m (9.8ft)

TC 3MCAT6 EU SAP: 3265146 US SAP: 12939582

### 5m (16.4ft)

TC 5MCAT6 EU SAP: 3265147 US SAP: 12939583

### 10m (32.8ft) END OF LIFE

TC 10MCAT6 EU SAP: 3265148 US SAP: 12939584

## SPECIFICATIONS

### TC 0.5MCAT6 White CAT6 Cable 0.5m (1.6ft)

#### INSULATION

HDPE, diameter: 0.97 mm (0.04")

#### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

#### CONDUCTOR THICKNESS

24AWG (7/0.2)

#### BANDWIDTH

250MHz

#### IMPEDANCE ( $\Omega$ )

100 $\pm$ 15

#### DELAY SKEW @ 20°C(NS/100M)

$\leq$ 45

#### PACKAGED WEIGHT

0.04 kg (0.09 lb)

#### PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

#### U/UTP (UNSCREENED)

#### STRANDED BARE COPPER CONDUCTORS

#### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 1MCAT6 White CAT6 Cable 1m (3.2ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.06 kg (0.13 lb)

### PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 2MCAT6 White CAT6 Cable 2m (6.5ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.10 kg (0.22 lb)

### PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 3MCAT6 White CAT6 Cable 3m (9.8ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.14 kg (0.3 lb)

### PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 5MCAT6 White CAT6 Cable 5m (16.4ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.23 kg (0.31 lb)

### PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 10MCAT6 White CAT6 Cable 10m (32.8ft)

---

### **INSULATION**

HDPE, diameter: 0.97 mm (0.04")

### **SHEATH**

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### **CONDUCTOR THICKNESS**

24AWG (7/0.2)

### **BANDWIDTH**

250MHz

### **IMPEDANCE ( $\Omega$ )**

100±15

### **DELAY SKEW @ 20°C(NS/100M)**

≤45

### **PACKAGED WEIGHT**

0.43 kg (0.95 lb)

### **PACKAGED DIMENSIONS**

220 mm x 270 mm (8.6" x 10.6")

### **U/UTP (UNSCREENED)**

### **STRANDED BARE COPPER CONDUCTORS**

### **GOLD-PLATED RJ45 BOOTED CONNECTORS**