



Braided HDMI Cable 1.5m (4.9ft)

TC 1.5MHDMI/HQ EU SAP: 4911588 US SAP: 13557638

vav.link/tc_1-5mhdmi-hq

Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.

IMAGE

Product Images

ZIP 1.13 MB

files.visionaudiovisual.com/products/TC_1-5MHDMI-HQ/images/TC_1-5MHDMI-HQ.zip

Image 1

PNG 1.15 MB

files.visionaudiovisual.com/products/TC_1-5MHDMI-HQ/images/TC_1-5MHDMI-HQ-1.png

SPECIFICATIONS

HDMI VERSION

v2.0 (4K @ 60Hz)

SHEATH OUTER DIAMETER

7.8 mm (0.31")

CONDUCTOR THICKNESS

28 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.21 kg (0.46 lb)

PRODUCT WEIGHT

0.14 kg (0.31 lb)

PACKAGED DIMENSIONS

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

COLOUR

Braided

CONNECTORS

GOLD-PLATED

DATA TRANSFER RATE

18 Gbit/s

BANDWIDTH

340 MHz

TYPE OF SHIELDING

Double Shielded

AUDIO RETURN CHANNEL (ARC)

Yes

4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET