



USB-C is the latest USB connector. It has a smaller reversible plug which supports USB 3.1 signal.

This type also supports the Thunderbolt 3.0 signal, which now uses a USB-C cable (Note: Bandwidth only goes up to 10 Gbps, as with most USB-C cables).

1m (3.2ft) END OF LIFE

TC 1MUSBC EU SAP: 4322264 US SAP: 12939452

1.5m (4.9ft) END OF LIFE AUGUST 2021

TC 1.5MUSBC EU SAP: 4322265 US SAP: 12939453

4m (13.1ft)

TC 4MUSBC EU SAP: 4880388 US SAP: 13445504

WCD Compatible

Tested and approved for use with Avocor products.

SPECIFICATIONS

TC 1MUSBC White USB-C Cable 1m (3.2ft)

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

22+30AWG

BANDWIDTH

5Gbit/s

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.04 kg (0.09 lb)

PRODUCT WEIGHT

0.033 kg (0.07 lb)

PACKAGED DIMENSIONS

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

POWER

60 watts

USB 3.1 CABLE

NICKEL-PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

TC 1.5MUSBC White USB-C Cable 1.5m (4.9ft)

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

22+30AWG

BANDWIDTH

5Gbit/s

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.06 kg (0.13 lb)

PRODUCT WEIGHT

0.052 kg (0.11 lb)

PACKAGED DIMENSIONS

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

POWER

60 watts

USB 3.1 CABLE**NICKEL-PLATED CONNECTORS**

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

TC 4MUSBC White USB-C Cable 4m (13.1ft)

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

22+30AWG

BANDWIDTH

10 Gbps

CHARGING CURRENT

3 A

POWER

60 watts

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.1 kg (0.22 lb)

PRODUCT WEIGHT

0.052 kg (0.11 lb)

PACKAGED DIMENSIONS

270 mm x 220 mm x 20 mm (10.6" x 8.7" x 0.8")

USB 3.1 CABLE**NICKEL-PLATED CONNECTORS**

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB