



0.5m (1.6ft)

TC 0.5MCAT6/BL EU SAP: 4911589 US SAP: 13557676

10m (32.8ft)

TC 10MCAT6/BL EU SAP: 4911594 US SAP: 13557614

1m (3.2ft)

TC 1MCAT6/BL EU SAP: 4911590 US SAP: 13557677

2m (6.5ft)

TC 2MCAT6/BL EU SAP: 4911591 US SAP: 13557678

3m (9.8ft)

TC 3MCAT6/BL EU SAP: 4911592 US SAP: 13557612

5m (16.4ft)

TC 5MCAT6/BL EU SAP: 4911593 US SAP: 13557613

SPECIFICATIONS

TC 0.5MCAT6/BL Black CAT6 Cable 0.5m (1.6ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PRODUCT WEIGHT

0.02 kg (0.04 lb)

PACKAGED WEIGHT

0.04 kg (0.09 lb)

PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

COLOUR

Black

WARRANTY

Lifetime return-to-base

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 10MCAT6/BL Black CAT6 Cable 10m (32.8ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PRODUCT WEIGHT

0.44 kg (0.97 lb)

PACKAGED WEIGHT

0.46 kg (1.01 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

COLOUR

Black

WARRANTY

Lifetime return-to-base

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 1MCAT6/BL Black CAT6 Cable 1m (3.2ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PRODUCT WEIGHT

0.04 kg (0.09 lb)

PACKAGED WEIGHT

0.06 kg (0.13 lb)

PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

COLOUR

Black

WARRANTY

Lifetime return-to-base

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 2MCAT6/BL Black CAT6 Cable 2m (6.5ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PRODUCT WEIGHT

0.09 kg (0.2 lb)

PACKAGED WEIGHT

0.10 kg (0.22 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

COLOUR

Black

WARRANTY

Lifetime return-to-base

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 3MCAT6/BL Black CAT6 Cable 3m (9.8ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PRODUCT WEIGHT

0.13 kg (0.29 lb)

PACKAGED WEIGHT

0.15 kg (0.33 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

COLOUR

Black

WARRANTY

Lifetime return-to-base

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 5MCAT6/BL Black CAT6 Cable 5m (16.4ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PRODUCT WEIGHT

0.22 kg (0.49 lb)

PACKAGED WEIGHT

0.23 kg (0.5 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

COLOUR

Black

WARRANTY

Lifetime return-to-base

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS