



### 0.5m (1.6ft) **END OF LIFE**

TC 0.5MCAT6/HQ EU SAP: 4911628 US SAP: 13557630

### 1m (3.2ft) **END OF LIFE**

TC 1MCAT6/HQ EU SAP: 4911629 US SAP: 13557631

### 2m (6.5ft) **END OF LIFE**

TC 2MCAT6/HQ EU SAP: 4911630 US SAP: 13557632

### 3m (9.8ft) **END OF LIFE**

TC 3MCAT6/HQ EU SAP: 4911583 US SAP: 13557633

### 5m (16.4ft) **END OF LIFE AUGUST 2021**

TC 5MCAT6/HQ EU SAP: 4911584 US SAP: 13557634

### 10m (32.8ft) **END OF LIFE AUGUST 2021**

TC 10MCAT6/HQ EU SAP: 4911585 US SAP: 13557635

## SPECIFICATIONS

### TC 0.5MCAT6/HQ Braided CAT6 Cable 0.5m (1.6ft)

#### INSULATION

HDPE, diameter: 0.97 mm (0.04")

#### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

#### CONDUCTOR THICKNESS

24AWG (7/0.2)

#### BANDWIDTH

250MHz

#### IMPEDANCE ( $\Omega$ )

100 $\pm$ 15

#### DELAY SKEW @ 20°C(NS/100M)

$\leq$ 45

#### PACKAGED WEIGHT

0.04 kg (0.09 lb)

#### PRODUCT WEIGHT

0.02 kg (0.04 lb)

#### PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

#### COLOUR

Braided

#### U/UTP (UNSCREENED)

#### STRANDED BARE COPPER CONDUCTORS

#### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 1MCAT6/HQ Braided CAT6 Cable 1m (3.2ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.06 kg (0.13 lb)

### PRODUCT WEIGHT

0.05 kg (0.11 lb)

### PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

### COLOUR

Braided

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 2MCAT6/HQ Braided CAT6 Cable 2m (6.5ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.10 kg (0.22 lb)

### PRODUCT WEIGHT

0.09 kg (0.19 lb)

### PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

### COLOUR

Braided

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 3MCAT6/HQ Braided CAT6 Cable 3m (9.8ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.15 kg (0.33 lb)

### PRODUCT WEIGHT

0.14 kg (0.31 lb)

### PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

### COLOUR

Braided

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 5MCAT6/HQ Braided CAT6 Cable 5m (16.4ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.24 kg (0.53 lb)

### PRODUCT WEIGHT

0.23 kg (0.31 lb)

### PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

### COLOUR

Braided

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS

## TC 10MCAT6/HQ Braided CAT6 Cable 10m (32.8ft)

---

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.47 kg (1.04 lb)

### PRODUCT WEIGHT

0.45 kg (0.99 lb)

### PACKAGED DIMENSIONS

182 mm x 182 mm x 52 mm (7.2" x 7.2" x 2.0")

### COLOUR

Braided

### U/UTP (UNSCREENED)

### STRANDED BARE COPPER CONDUCTORS

### GOLD-PLATED RJ45 BOOTED CONNECTORS