



Braided HDMI Cable 15m (49.2ft)

TC 15MHDMI/HQ EU SAP: 4911407 US SAP: 13557591

vav.link/tc_15mhdmi-hq

Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.

IMAGE

Product Images

ZIP 1.29 MB

files.visionaudiovisual.com/products/TC2_15MHDMI/images/TC2_15MHDMI.zip

Product Images

ZIP 1.13 MB

files.visionaudiovisual.com/products/TC_15MHDMI-HQ/images/TC_15MHDMI-HQ.zip

Image 1

PNG 1.15 MB

files.visionaudiovisual.com/products/TC_15MHDMI-HQ/images/TC_15MHDMI-HQ-1.png

SPECIFICATIONS

HDMI VERSION

v1.4 (4K @ 30Hz)

SHEATH OUTER DIAMETER

9.5 mm (0.37")

CONDUCTOR THICKNESS

24 AWG

PACKAGED WEIGHT

1.79 kg (3.95 lb)

PRODUCT WEIGHT

1.65 kg (3.64 lb)

PACKAGED DIMENSIONS

200 mm x 200 mm x 90 mm (7.9" x 7.9" x 3.5")

COLOUR

Braided

CONNECTORS

GOLD-PLATED

DATA TRANSFER RATE

18 Gbit/s

BANDWIDTH

340 MHz

TYPE OF SHIELDING

Double Shielded

AUDIO RETURN CHANNEL (ARC)

Yes

4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET