



USB-A is the type of connector which plugs into your laptop.
USB-B is the end that plugs into your printer.

High quality braided shield and ferrite core connector at both ends to shield against EMF and RF interference.

1m (3.2ft) **END OF LIFE AUGUST 2021**

TC 1MUSB/HQ EU SAP: 4911570 US SAP: 13557562

2m (6.5ft) **END OF LIFE AUGUST 2021**

TC 2MUSB/HQ EU SAP: 4911571 US SAP: 13557563

3m (9.8ft) **END OF LIFE AUGUST 2021**

TC 3MUSB/HQ EU SAP: 4911572 US SAP: 13557564

5m (16.4ft) **END OF LIFE SEPTEMBER 2020**

TC 5MUSB/HQ EU SAP: 4911573 US SAP: 13557565

15m (49.2ft) **END OF LIFE**

TC 15MUSB+/HQ EU SAP: 4911575 US SAP: 13557567

10m (32.8ft) **END OF LIFE DECEMBER 2020**

TC 10MUSB+/HQ EU SAP: 4911574 US SAP: 13557566

SPECIFICATIONS

TC 1MUSB/HQ Braided USB 2.0 Cable 1m (3.2ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.10 kg (0.22 lb)

PRODUCT WEIGHT

0.05 kg (0.11 lb)

PACKAGED DIMENSION

150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

COLOUR

Braided

HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

TC 2MUSB/HQ Braided USB 2.0 Cable 2m (6.5ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.14 kg (0.31 lb)

PRODUCT WEIGHT

0.07 kg (0.15 lb)

PACKAGED DIMENSION

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

COLOUR

Braided

FERRITE CORE USB-A END

HIGH SPEED USB 2.0 CABLE

GOLD-PLATED CONNECTORS

TC 3MUSB/HQ Braided USB 2.0 Cable 3m (9.8ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.17 kg (0.37 lb)

PRODUCT WEIGHT

0.10 kg (0.22 lb)

PACKAGED DIMENSION

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

COLOUR

Braided

HIGH SPEED USB 2.0 CABLE

BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE

GOLD-PLATED CONNECTORS

TC 5MUSB/HQ Braided USB 2.0 Cable 5m (16.4ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

v> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.26 kg (0.57 lb)

PRODUCT WEIGHT

0.19 kg (0.42 lb)

PACKAGED DIMENSION

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

COLOUR

Braided

HIGH SPEED USB 2.0 CABLE

BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE

GOLD-PLATED CONNECTORS

TC 15MUSB+/HQ Braided USB 2.0 Cable 15m (49.2ft) with active booster

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.56 kg (1.23 lb)

PRODUCT WEIGHT

0.42 kg (0.93 lb)

PACKAGED DIMENSION

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

COLOUR

Braided

HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

TC 10MUSB+/HQ Braided USB 2.0 Cable 10m (32.8ft) with active booster

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.43 kg (0.95 lb)

PRODUCT WEIGHT

0.29 kg (0.64 lb)

PACKAGED DIMENSION

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

COLOUR

Braided

HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS