



Plugs into the VGA socket on your computer - which is often blue - and connects to a display device at the other end.

For VGA cables pre-terminated for Vision's Techconnect Modular Faceplate click [here](#).

**1m (3.2ft)** END OF LIFE

TC 1MVGAP/BL EU SAP: 4911609 US SAP: 13557576

**2m (6.5ft)** END OF LIFE

TC 2MVGAP/BL EU SAP: 4911610 US SAP: 13557577

**3m (9.8ft)** END OF LIFE

TC 3MVGAP/BL EU SAP: 4911611 US SAP: 13557578

**5m (16.4ft)** END OF LIFE

TC 5MVGAP/BL EU SAP: 4911612 US SAP: 13557579

**10m (32.8ft)** END OF LIFE

TC 10MVGAP/BL EU SAP: 4911613 US SAP: 13557643

**15m (49.2ft)** END OF LIFE

TC 15MVGAP/BL EU SAP: 4911614 US SAP: 13557644

## SPECIFICATIONS

### TC 1MVGAP/BL Black VGA Cable 1m (3.2ft)

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.21 kg (0.46 lb)

**PRODUCT WEIGHT**

0.14 kg (0.31 lb)

**PACKAGED DIMENSIONS**

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

**COLOR**

Black

**LENGTH**

1m (3.2ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**

**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID**

**AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 2MVGAP/BL Black VGA Cable 2m (6.5ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.34 kg (0.75 lb)

**PRODUCT WEIGHT**

0.24 kg (0.53 lb)

**PACKAGED DIMENSIONS**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**COLOR**

Black

**LENGTH**

2m (6.5ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 3MVGAP/BL Black VGA Cable 3m (9.8ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.43 kg (0.95 lb)

**PRODUCT WEIGHT**

0.33 kg (0.73 lb)

**PACKAGED DIMENSIONS**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**COLOR**

Black

**LENGTH**

3m (9.8ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 5MVGAP/BL Black VGA Cable 5m (16.4ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.66 kg (1.46 lb)

**PRODUCT WEIGHT**

0.56 kg (1.23 lb)

**PACKAGED DIMENSIONS**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**COLOR**

Black

**LENGTH**

5m (16.4ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 10MVGAP/BL Black VGA Cable 10m (32.8ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

1.05 kg (2.3 lbs)

**PRODUCT WEIGHT**

0.91 kg (2.0 lbs)

**PACKAGED DIMENSIONS**

200 mm x 200 mm x 90 mm (7.1" x 7.1" x 2.8")

**COLOR**

Black

**LENGTH**

10m (32.8ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 15MVGAP/BL Black VGA Cable 15m (49.2ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

1.65 kg (3.64 lb)

**PRODUCT WEIGHT**

1.51 kg (3.33 lbs)

**PACKAGED DIMENSIONS**

200 mm x 200 mm x 90 mm (7.9" x 7.9" x 3.5")

**COLOR**

Black

**LENGTH**

15m (49.2ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**