



Plugs into the VGA socket on your computer - which is often blue - and connects to a display device at the other end.

**1m (3.2ft)** **END OF LIFE SEPTEMBER 2021**

TC 1MVGAP/HQ EU SAP: 4911564 US SAP: 13557598

**2m (6.5ft)** **END OF LIFE SEPTEMBER 2021**

TC 2MVGAP/HQ EU SAP: 4911565 US SAP: 13557599

**3m (9.8ft)** **END OF LIFE**

TC 3MVGAP/HQ EU SAP: 4911566 US SAP: 13557600

**5m (16.4ft)** **END OF LIFE**

TC 5MVGAP/HQ EU SAP: 4911567 US SAP: 13557539

**10m (32.8ft)** **END OF LIFE**

TC 10MVGAP/HQ EU SAP: 4911568 US SAP: 13557540

**15m (49.2ft)** **END OF LIFE**

TC 15MVGAP/HQ EU SAP: 4911569 US SAP: 13557561

## SPECIFICATIONS

### TC 1MVGAP/HQ Braided VGA Cable 1m (3.2ft)

**SHEATH: PVC, OUTER DIAMETER**

8.5 mm (0.33")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.22 kg (0.49 lb)

**PRODUCT WEIGHT**

0.15 kg (0.33 lb)

**PACKAGED DIMENSIONS**

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

**COLOUR**

Braided

**LENGTH**

1m (3.2ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**

**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID**

**AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 2MVGAP/HQ Braided VGA Cable 2m (6.5ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.5 mm (0.33")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.36 kg (0.79 lb)

**PRODUCT WEIGHT**

0.26 kg (0.57 lb)

**PACKAGED DIMENSIONS**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**COLOUR**

Braided

**LENGTH**

2m (6.5ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**

**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID**

**AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE  
BRAIDED SHIELD**

## TC 3MVGAP/HQ Braided VGA Cable 3m (9.8ft)

---

**COLOUR**

Braided

**SHEATH: PVC, OUTER DIAMETER**

8.5 mm (0.33")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.36 kg (0.79 lb)

**PRODUCT WEIGHT.**

0.46 kg (1.01 lb)

**PACKAGED DIMENSIONS**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**LENGTH**

3m (9.8ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**

**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID**

**AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE  
BRAIDED SHIELD**

## TC 5MVGAP/HQ Braided VGA Cable 5m (16.4ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.5 mm (0.33")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.70 kg (1.54 lb)

**PRODUCT WEIGHT**

0.60 kg (1.32 lb)

**PACKAGED DIMENSIONS**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**COLOUR**

Braided

**LENGTH**

5m (16.4ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**

**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID**

**AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE  
BRAIDED SHIELD**

## TC 10MVGAP/HQ Braided VGA Cable 10m (32.8ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.5 mm (0.33")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

1.12 kg (2.47 lb)

**PRODUCT WEIGHT**

0.98 kg (2.16 lb)

**PACKAGED DIMENSIONS**

200 mm x 200 mm x 90 mm (7.9" x 7.9" x 3.5")

**COLOUR**

Braided

**LENGTH**

10m (32.8ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE  
BRAIDED SHIELD**

## TC 15MVGAP/HQ Braided VGA Cable 15m (49.2ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.5 mm (0.33")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

1.75 kg (3.86 lb)

**PRODUCT WEIGHT**

1.61 kg (3.54 lb)

**PACKAGED DIMENSIONS**

200 mm x 200 mm x 90 mm (7.9" x 7.9" x 3.5")

**COLOUR**

Braided

**LENGTH**

15m (49.2ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE  
BRAIDED SHIELD**