



0.5m (1.6ft)

TC 0.5MCAT6 EU SAP: 3265140 US SAP: 12939555

1m (3.2ft)

TC 1MCAT6 EU SAP: 3265141 US SAP: 12939580

2m (6.5ft)

TC 2MCAT6 EU SAP: 3265142 US SAP: 12939581

3m (9.8ft)

TC 3MCAT6 EU SAP: 3265146 US SAP: 12939582

5m (16.4ft)

TC 5MCAT6 EU SAP: 3265147 US SAP: 12939583

10m (32.8ft) END OF LIFE

TC 10MCAT6 EU SAP: 3265148 US SAP: 12939584

SPECIFICATIONS

TC 0.5MCAT6 White CAT6 Cable 0.5m (1.6ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.04 kg (0.09 lb)

PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 1MCAT6 White CAT6 Cable 1m (3.2ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.06 kg (0.13 lb)

PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 2MCAT6 White CAT6 Cable 2m (6.5ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.10 kg (0.22 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 3MCAT6 White CAT6 Cable 3m (9.8ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.14 kg (0.3 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 5MCAT6 White CAT6 Cable 5m (16.4ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.23 kg (0.31 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 10MCAT6 White CAT6 Cable 10m (32.8ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.43 kg (0.95 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS