



Note that Thunderbolt® uses the Mini-DP connector. In addition to carrying DisplayPort signal Thunderbolt also carries data. This cable only supports DisplayPort.

1m (3.2ft) **END OF LIFE**

TC 1MMDPDP EU SAP: 4500874 US SAP: 13041727

2m (6.5ft) **END OF LIFE**

TC 2MMDPDP EU SAP: 4500875 US SAP: 13041728

SPECIFICATIONS

TC 1MMDPDP White Mini-DisplayPort to DisplayPort Cable 1m (3.2ft)

MAXIMUM RESOLUTION

4k @ 60 Hz

SHEATH: OUTER DIAMETER

5.5 mm (0.22")

CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.07 kg (0.15 lb)

PACKAGED DIMENSIONS

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

BI-DIRECTIONAL. SUPPORTS MDP-TO-DP OR DP-TO-MDP

4K COMPLIANT

GOLD-PLATED CONNECTORS

SUPPORTS 1 MBPS BIDIRECTIONAL AUXILIARY CHANNEL

SUPPORTS HOTPLUG

TC 2MMDPDP White Mini-DisplayPort to DisplayPort Cable 2m (6.5ft)

MAXIMUM RESOLUTION

4k @ 60 Hz

SHEATH: OUTER DIAMETER

5.5 mm (0.22")

CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.10 kg (0.22 lb)

PACKAGED DIMENSIONS

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

BI-DIRECTIONAL. SUPPORTS MDP-TO-DP OR DP-TO-MDP

4K COMPLIANT

GOLD-PLATED CONNECTORS

SUPPORTS 1 MBPS BIDIRECTIONAL AUXILIARY CHANNEL

SUPPORTS HOTPLUG