



USB-A is the type of connector which plugs into your laptop. USB-B is the end that plugs into your printer.

High quality braided shield and ferrite core connector at both ends to shield against EMF and RF interference.

### 1m (3.2ft)

TC 1MUSB/BL EU SAP: 4911615 US SAP: 13557645

### 2m (6.5ft)

TC 2MUSB/BL EU SAP: 4911616 US SAP: 13557646

### 3m (9.8ft)

TC 3MUSB/BL EU SAP: 4911617 US SAP: 13557647

### 5m (16.4ft)

TC 5MUSB/BL EU SAP: 4911618 US SAP: 13557648

### 15m (49.2ft)

TC 15MUSB+/BL EU SAP: 4911620 US SAP: 13557650

### 10m (32.8ft)

TC 10MUSB+/BL EU SAP: 4911619 US SAP: 13557649

## SPECIFICATIONS

### TC 1MUSB/BL Black USB 2.0 Cable 1m (3.2ft)

#### INSULATION

HDPE

#### SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

#### CONDUCTOR THICKNESS

28+24AWG

#### BANDWIDTH

480Mbit/s

#### SHEILDING

> 65% coverage braided shield

#### COMPLIANCE

RoHS, CE, FCC

#### PACKAGED WEIGHT

0.11 kg (0.24 lb)

#### PRODUCT WEIGHT

0.06 kg (0.13 lb)

#### PACKAGED DIMENSION

150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

#### COLOR

Black

#### HIGH SPEED USB 2.0 CABLE

#### FERRITE CORE AT CONNECTOR A (COMPUTER) END

#### GOLD-PLATED CONNECTORS

## TC 2MUSB/BL Black USB 2.0 Cable 2m (6.5ft)

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.16 kg (0.35 lb)

**PRODUCT WEIGHT**

0.09 kg (0.2 lb)

**PACKAGED DIMENSION**

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

**COLOR**

Black

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****HIGH SPEED USB 2.0 CABLE****GOLD-PLATED CONNECTORS**

## TC 3MUSB/BL Black USB 2.0 Cable 3m (9.8ft)

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.15 kg (0.33 lb)

**PRODUCT WEIGHT**

0.14 kg (0.31 lb)

**PACKAGED DIMENSION**

115 x 40 x 160 mm (4.5" x 1.6" x 6.3")

**COLOR**

Black

**HIGH SPEED USB 2.0 CABLE****BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

## TC 5MUSB/BL Black USB 2.0 Cable 5m (16.4ft)

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

v> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.31 kg (0.68 lb)

**PRODUCT WEIGHT**

0.24 kg (0.53 lb)

**PACKAGED DIMENSION**

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

**COLOR**

Black

**HIGH SPEED USB 2.0 CABLE****BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

## TC 15MUSB+/BL Black USB 2.0 Cable 15m (49.2ft) with active booster

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.63 kg (1.39 lb)

**PRODUCT WEIGHT**

0.53 kg (1.17 lb)

**PACKAGED DIMENSION**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**COLOR**

Black

**HIGH SPEED USB 2.0 CABLE**

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**

## TC 10MUSB+/BL Black USB 2.0 Cable 10m (32.8ft) with active booster

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.47 kg (1.04 lb)

**PRODUCT WEIGHT**

0.37 kg (0.81 lb)

**PACKAGED DIMENSION**

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

**COLOR**

Black

**HIGH SPEED USB 2.0 CABLE**

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**