



USB-C is the latest USB connector. It has a smaller reversible plug which supports USB 3.1 signal.

They also support the Thunderbolt 3.0 signal which now uses USB-C cable (Note Bandwidth only goes up to 10Gbps as with most USB-C cables).

Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.

WCD Compatible

Tested and approved for use with Avocor products.

SPECIFICATIONS

SHEATH: PVC, OUTER DIAMETER

5.0 mm (0.2")

CONDUCTOR THICKNESS

22+30AWG

BANDWIDTH

5Gbit/s

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.09 kg (0.2 lb)

PRODUCT WEIGHT

0.04 kg (0.09 lb)

PACKAGED DIMENSIONS

150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

COLOUR

Braided

POWER

60 watts

USB 3.1 CABLE

NICKEL-PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB