



On one end: USB A - plugs into the old connector on your laptop and carries USB 3.0 signal.

On the other end: USB type C - the new smaller reversible USB plug which supports USB 3.1 signal.

1m (3.2ft) END OF LIFE AUGUST 2021

TC 1MUSBCA/HQ EU SAP: 4911579 US SAP: 13557656

2m (6.5ft) END OF LIFE AUGUST 2021

TC 2MUSBCA/HQ EU SAP: 4911580 US SAP: 13557657

SPECIFICATIONS

TC 1MUSBCA/HQ Braided USB-C to USB 3.0A Cable 1m (3.2ft)

SHEATH: PVC, OUTER DIAMETER

4.5 mm (0.18")

CONDUCTOR THICKNESS

22+30 AWG

BANDWIDTH

480Mbit/s

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.08 kg (0.17 lb)

PRODUCT WEIGHT

0.03 kg (0.06 lb)

PACKAGED DIMENSIONS

150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

COLOUR

Braided

LENGTH

1m (3.2ft)

USB 3.0 CABLE

NICKEL-PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

TC 2MUSBCA/HQ Braided USB-C to USB 3.0A Cable 2m (6.5ft)

SHEATH: PVC, OUTER DIAMETER

4.5 mm (0.18")

CONDUCTOR THICKNESS

22+30 AWG

BANDWIDTH

480Mbit/s

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.06 kg (0.13 lb)

PRODUCT WEIGHT

0.11 kg (0.24 lb)

PACKAGED DIMENSIONS

150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

COLOUR

Braided

LENGTH

2m (6.5ft)

USB 3.0 CABLE**NICKEL-PLATED CONNECTORS**

**SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT
OR HDMI SIGNAL INSTEAD OF USB**