



1m (3.2ft) **END OF LIFE**

TC 1MUSBM EU SAP: 3265180 US SAP: 13332300

2m (6.5ft) **END OF LIFE**

TC 2MUSBM EU SAP: 4432258 US SAP: 13332301

3m (9.8ft) **END OF LIFE AUGUST 2021**

TC 3MUSBM EU SAP: 4432259 US SAP: 13332296

SPECIFICATIONS

TC 1MUSBM White USB 2.0 Micro-B to USB-A Cable 1m (3.2ft)

INSULATION

white rubber

SHEATH: PVC, OUTER DIAMETER

3.8 mm (0.14")

CONDUCTOR THICKNESS

28+20AWG

BANDWIDTH

480Mbit/s

CHARGING CURRENT

3A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.03 kg (0.07 lb)

PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

HIGH SPEED USB 2.0 CABLE

NIKEL-PLATED CONNECTORS WITH GOLD-PLATED PINS

TC 2MUSBM White USB 2.0 Micro-B to USB-A Cable 2m (6.5ft)

INSULATION

white rubber

SHEATH: PVC, OUTER DIAMETER

3.8 mm (0.14")

CONDUCTOR THICKNESS

28+20AWG

BANDWIDTH

480Mbit/s

CHARGING CURRENT

3A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.06 kg (0.13 lb)

PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

HIGH SPEED USB 2.0 CABLE

NIKEL-PLATED CONNECTORS WITH GOLD-PLATED PINS

TC 3MUSBM White USB 2.0 Micro-B to USB-A Cable 3m (9.8ft)

INSULATION

white rubber

SHEATH: PVC, OUTER DIAMETER

3.8 mm (0.14")

CONDUCTOR THICKNESS

28+20AWG

BANDWIDTH

480Mbit/s

CHARGING CURRENT

1.1A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.08 kg (0.18 lb)

PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

HIGH SPEED USB 2.0 CABLE

NIKEL-PLATED CONNECTORS WITH GOLD-PLATED PINS

