



# Braided DisplayPort Cable 2m

TC 2MDP/HQ EU SAP: 4911409 US SAP: 13557593

[vav.link/tc\\_2mdp-hq](http://vav.link/tc_2mdp-hq)



## Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

## Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.



VISION

## IMAGE

---

Image 1

**PNG 707.06 KB**

[files.visionaudiovisual.com/products/TC\\_2MDP-HQ/images/TC\\_2MDP-HQ\\_1.png](files.visionaudiovisual.com/products/TC_2MDP-HQ/images/TC_2MDP-HQ_1.png)

Image 2

**PNG 360.26 KB**

[files.visionaudiovisual.com/products/TC\\_2MDP-HQ/images/TC\\_2MDP-HQ\\_2.png](files.visionaudiovisual.com/products/TC_2MDP-HQ/images/TC_2MDP-HQ_2.png)

Image 3

**PNG 680.14 KB**

[files.visionaudiovisual.com/products/TC\\_2MDP-HQ/images/TC\\_2MDP-HQ\\_3.png](files.visionaudiovisual.com/products/TC_2MDP-HQ/images/TC_2MDP-HQ_3.png)

## SPECIFICATIONS

---

### MAXIMUM RESOLUTION

4k @ 60 Hz

### SHEATH OUTER DIAMETER

6.0 mm (0.24")

### CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

### PACKAGED WEIGHT

0.17 kg (0.37 lb)

### PRODUCT WEIGHT

0.12 kg (0.26 lb)

### PACKAGED DIMENSIONS

160 mm x 160 mm x 43 mm (6.3" x 6.3" x 1.7")

### COLOUR

Braided

### 4K COMPLIANT

### GOLD-PLATED CONNECTORS

SUPPORTS 1 MBPS BIDIRECTIONAL AUXILIARY CHANNEL

SUPPORTS HOTPLUG

VERSION 1.2