



Allows PCs with 'Dual-Mode' DisplayPort (DP++) outputs to connect to displays with HDMI inputs.

Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.

SPECIFICATIONS

MAXIMUM RESOLUTION

4k @ 60 Hz (note: at time of writing no chipset supports 60Hz)

CONTACT RESISTANCE

2 ohm max

SHEATH OUTER DIAMETER

6.0 mm (0.24")

CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.17 kg (0.37 lb)

PRODUCT WEIGHT

0.12 kg (0.26 lb)

PACKAGED DIMENSION

160 mm x 160 mm x 43 mm (6.3" x 6.3" x 1.7")

COLOUR

Braided

4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET

HDMI 2.0 (ACTIVE CIRCUIT AT HDMI CONNECTOR)

GOLD-PLATED CONNECTORS

SUPPORTS HOTPLUG

NOT BI-DIRECTIONAL. DOES NOT CONVERT HDMI TO DP

PS176 CHIPSET