



Braided Mini-DisplayPort to HDMI Cable 2m (6.5ft)

TC 2MMDPHDMI/HQ EU SAP: 4911561 US SAP: 13557595

vav.link/tc_2mmdphdmi-hq

Allows PCs with 'Dual-Mode' DisplayPort (DP++) outputs to connect to displays with HDMI inputs.

Note that Thunderbolt® uses the Mini-DP connector. In addition to carrying DisplayPort signal Thunderbolt also carries data.



Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.



VISION

IMAGE

Product Images

ZIP 448.71 KB

files.visionaudiovisual.com/products/TC_2MMDPHDMI/images/TC_2MMDPHDMI.zip

Product Images

ZIP 1.68 MB

files.visionaudiovisual.com/products/TC_2MMDPHDMI-HQ/images/TC_2MMDPHDMI-HQ.zip

Image 2

PNG 813.90 KB

files.visionaudiovisual.com/products/TC_2MMDPHDMI-HQ/images/TC_2MMDPHDMI-HQ_2.png

Image 3

PNG 712.57 KB

files.visionaudiovisual.com/products/TC_2MMDPHDMI-HQ/images/TC_2MMDPHDMI-HQ_3.png

1 square

PNG 234.61 KB

files.visionaudiovisual.com/products/TC_2MMDPHDMI-HQ/images/TC_2MMDPHDMI-HQ_1_square.png

SPECIFICATIONS

MAXIMUM RESOLUTION

4k @ 60 Hz

CONTACT RESISTANCE

2 ohm max

SHEATH OUTER DIAMETER

6.0 mm (0.24")

CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.16 kg (0.35 lb)

PRODUCT WEIGHT

0.11 kg (0.24 lb)

PACKAGED DIMENSION

160 mm x 160 mm x 43 mm (6.3" x 6.3" x 1.7")

COLOUR

Braided

4K COMPLIANT

HDMI 2.0 (ACTIVE CIRCUIT AT HDMI CONNECTOR)

GOLD-PLATED CONNECTORS

SUPPORTS HOTPLUG

NOT BI-DIRECTIONAL. DOES NOT CONVERT HDMI TO DP

PS176 CHIPSET