



USB-A is the type of connector which plugs into your laptop. USB-B is the end that plugs into your printer.

High quality braided shield and ferrite core connector at both ends to shield against EMF and RF interference.

\*10m+ models have an in-line active booster (48 mm / 1.9" long x 25 mm / 0.98" wide) integrated half way along cable.

When used with Vision's Techconnect modular faceplate, we recommend using the TC2 USB+ active booster module with all cables longer than 5m (16.4 ft).

### 1m (3.2ft)

TC 1MUSB EU SAP: 3265177 US SAP: 12939570

### 2m (6.5ft)

TC 2MUSB EU SAP: 3265178 US SAP: 12939571

### 3m (9.8ft)

TC2 3MUSB EU SAP: 3004700 US SAP: 12939522

### 5m (16.4ft)

TC2 5MUSB EU SAP: 3004951 US SAP: 12939526

### 10m (32.8ft)

TC2 10MUSB+ EU SAP: 3244188 US SAP: 12939463

### 15m (49.2ft)

TC2 15MUSB+ EU SAP: 3004953 US SAP: 12939466

## SPECIFICATIONS

### TC 1MUSB White USB 2.0 Cable 1m (3.2ft)

#### INSULATION

HDPE

#### SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

#### CONDUCTOR THICKNESS

28+24AWG

#### BANDWIDTH

480Mbit/s

#### SHEILDING

> 65% coverage braided shield

#### COMPLIANCE

RoHS, CE, FCC

#### PACKAGED WEIGHT

0.04 kg (0.09 lb)

#### PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

#### HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

## TC 2MUSB White USB 2.0 Cable 2m (6.5ft)

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.08 kg (0.18 lb)

**PACKAGED DIMENSION**

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

**FERRITE CORES USB-A END****HIGH SPEED USB 2.0 CABLE****GOLD-PLATED CONNECTORS**

## TC2 3MUSB White USB 2.0 Cable 3m (9.8ft)

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.12 kg (0.26 lb)

**PACKAGED DIMENSION**

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

**COLOR**

White

**HIGH SPEED USB 2.0 CABLE****BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

## TC2 5MUSB White USB 2.0 Cable 5m (16.4ft)

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

v> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.22 kg (0.49 lb)

**PACKAGED DIMENSION**

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

**HIGH SPEED USB 2.0 CABLE****BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

## TC2 10MUSB+ White USB 2.0 Cable 10m (32.8ft) with active booster

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.35 kg (0.77 lb)

**PACKAGED DIMENSION**

180 x 170 x 70 mm (7.1" x 6.7" x 2.8")

**HIGH SPEED USB 2.0 CABLE****FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS**

## TC2 15MUSB+ White USB 2.0 Cable 15m (49.2ft) with active booster

---

**INSULATION**

HDPE

**SHEATH: PVC, OUTER DIAMETER**

4.5mm (0.18")

**CONDUCTOR THICKNESS**

28+24AWG

**BANDWIDTH**

480Mbit/s

**SHEILDING**

> 65% coverage braided shield

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.50 kg (1.1 lb)

**PACKAGED DIMENSION**

180 x 170 x 70 mm (7.1" x 6.7" x 2.8")

**HIGH SPEED USB 2.0 CABLE**

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**