



0.5m (1.6ft) **END OF LIFE**

TC 0.5MCAT6/HQ EU SAP: 4911628 US SAP: 13557630

1m (3.2ft) **END OF LIFE**

TC 1MCAT6/HQ EU SAP: 4911629 US SAP: 13557631

2m (6.5ft) **END OF LIFE**

TC 2MCAT6/HQ EU SAP: 4911630 US SAP: 13557632

3m (9.8ft) **END OF LIFE**

TC 3MCAT6/HQ EU SAP: 4911583 US SAP: 13557633

5m (16.4ft) **END OF LIFE AUGUST 2021**

TC 5MCAT6/HQ EU SAP: 4911584 US SAP: 13557634

10m (32.8ft) **END OF LIFE AUGUST 2021**

TC 10MCAT6/HQ EU SAP: 4911585 US SAP: 13557635

SPECIFICATIONS

TC 0.5MCAT6/HQ Braided CAT6 Cable 0.5m (1.6ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.04 kg (0.09 lb)

PRODUCT WEIGHT

0.02 kg (0.04 lb)

PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

COLOUR

Braided

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 1MCAT6/HQ Braided CAT6 Cable 1m (3.2ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.06 kg (0.13 lb)

PRODUCT WEIGHT

0.05 kg (0.11 lb)

PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

COLOUR

Braided

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 2MCAT6/HQ Braided CAT6 Cable 2m (6.5ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.10 kg (0.22 lb)

PRODUCT WEIGHT

0.09 kg (0.19 lb)

PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

COLOUR

Braided

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 3MCAT6/HQ Braided CAT6 Cable 3m (9.8ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.15 kg (0.33 lb)

PRODUCT WEIGHT

0.14 kg (0.31 lb)

PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

COLOUR

Braided

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 5MCAT6/HQ Braided CAT6 Cable 5m (16.4ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.24 kg (0.53 lb)

PRODUCT WEIGHT

0.23 kg (0.31 lb)

PACKAGED DIMENSIONS

162 mm x 162 mm x 42 mm (6.4" x 6.4" x 1.7")

COLOUR

Braided

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS

TC 10MCAT6/HQ Braided CAT6 Cable 10m (32.8ft)

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.47 kg (1.04 lb)

PRODUCT WEIGHT

0.45 kg (0.99 lb)

PACKAGED DIMENSIONS

182 mm x 182 mm x 52 mm (7.2" x 7.2" x 2.0")

COLOUR

Braided

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS