



Allows PCs with 'Dual-Mode' DisplayPort (DP++) outputs to connect to displays with HDMI inputs.

3m (9.8ft) **END OF LIFE AUGUST 2021**

TC 3MDPHDMI4K EU SAP: 4821709

2m (6.5ft) **END OF LIFE**

TC 2MDPHDMI4K EU SAP: 4821589

SPECIFICATIONS

TC 3MDPHDMI4K White DisplayPort to HDMI Cable 3m (9.8ft)

MAXIMUM RESOLUTION

4k @ 60 Hz

CONTACT RESISTANCE

2 ohm max

SHEATH OUTER DIAMETER

6.0 mm (0.24")

CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.15 kg (0.33 lb)

PACKAGED DIMENSION

220 mm x 270 mm (8.7" x 10.6")

4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET

HDMI 2.0 (ACTIVE CIRCUIT AT HDMI CONNECTOR)

GOLD-PLATED CONNECTORS

SUPPORTS HOTPLUG

NOT BI-DIRECTIONAL. DOES NOT CONVERT HDMI TO DP

TC 2MDPHDMI4K White DisplayPort to HDMI Cable 2m (6.5ft)

MAXIMUM RESOLUTION

4k @ 60 Hz

CONTACT RESISTANCE

2 ohm max

SHEATH OUTER DIAMETER

6.0 mm (0.24")

CONDUCTOR THICKNESS

30 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.11 kg (0.24 lb)

PACKAGED DIMENSION

220 mm x 270 mm (8.7" x 10.6")

4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET

HDMI 2.0 (ACTIVE CIRCUIT AT HDMI CONNECTOR)

GOLD-PLATED CONNECTORS

SUPPORTS HOTPLUG

NOT BI-DIRECTIONAL. DOES NOT CONVERT HDMI TO DP

