



USB-A is the type of connector which plugs into your laptop. USB-B is the end that plugs into your printer.

High quality braided shield and ferrite core connector at both ends to shield against EMF and RF interference.

1m (3.2ft)

TC 1MUSB/BL EU SAP: 4911615 US SAP: 13557645

2m (6.5ft)

TC 2MUSB/BL EU SAP: 4911616 US SAP: 13557646

3m (9.8ft)

TC 3MUSB/BL EU SAP: 4911617 US SAP: 13557647

5m (16.4ft)

TC 5MUSB/BL EU SAP: 4911618 US SAP: 13557648

15m (49.2ft)

TC 15MUSB+/BL EU SAP: 4911620 US SAP: 13557650

10m (32.8ft)

TC 10MUSB+/BL EU SAP: 4911619 US SAP: 13557649

SPECIFICATIONS

TC 1MUSB/BL Black USB 2.0 Cable 1m (3.2ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.11 kg (0.24 lb)

PRODUCT WEIGHT

0.06 kg (0.13 lb)

PACKAGED DIMENSION

150 mm x 150 mm x 30 mm (5.9" x 5.9" x 1.2")

COLOR

Black

HIGH SPEED USB 2.0 CABLE

FERRITE CORE AT CONNECTOR A (COMPUTER) END

GOLD-PLATED CONNECTORS

TC 2MUSB/BL Black USB 2.0 Cable 2m (6.5ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.16 kg (0.35 lb)

PRODUCT WEIGHT

0.09 kg (0.2 lb)

PACKAGED DIMENSION

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

COLOR

Black

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**HIGH SPEED USB 2.0 CABLE****GOLD-PLATED CONNECTORS**

TC 3MUSB/BL Black USB 2.0 Cable 3m (9.8ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.15 kg (0.33 lb)

PRODUCT WEIGHT

0.14 kg (0.31 lb)

PACKAGED DIMENSION

115 x 40 x 160 mm (4.5" x 1.6" x 6.3")

COLOR

Black

HIGH SPEED USB 2.0 CABLE**BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

TC 5MUSB/BL Black USB 2.0 Cable 5m (16.4ft)

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

v> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.31 kg (0.68 lb)

PRODUCT WEIGHT

0.24 kg (0.53 lb)

PACKAGED DIMENSION

160 mm x 160 mm x 45 mm (6.3" x 6.3" x 1.8")

COLOR

Black

HIGH SPEED USB 2.0 CABLE**BRAIDED SHIELD AND FERRITE CORE AT CONNECTOR A (COMPUTER) END TO SHIELD AGAINST EMF AND RF INTERFERENCE****GOLD-PLATED CONNECTORS**

TC 15MUSB+/BL Black USB 2.0 Cable 15m (49.2ft) with active booster

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.63 kg (1.39 lb)

PRODUCT WEIGHT

0.53 kg (1.17 lb)

PACKAGED DIMENSION

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

COLOR

Black

HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

TC 10MUSB+/BL Black USB 2.0 Cable 10m (32.8ft) with active booster

INSULATION

HDPE

SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

CONDUCTOR THICKNESS

28+24AWG

BANDWIDTH

480Mbit/s

SHEILDING

> 65% coverage braided shield

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.47 kg (1.04 lb)

PRODUCT WEIGHT

0.37 kg (0.81 lb)

PACKAGED DIMENSION

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

COLOR

Black

HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS