



On one end: USB A - plugs into the old connector on your laptop and carries USB 3.0 signal.

On the other end: USB type C - the new smaller reversible USB plug which supports USB 3.1 signal.

1m (3.2ft)

TC 1MUSBCA EU SAP: 4322261 US SAP: 12938689

2m (6.5ft)

TC 2MUSBCA EU SAP: 4322262 US SAP: 12938690

3m (9.8ft) END OF LIFE

TC 3MUSBCA EU SAP: 4322263 US SAP: 12939451

SPECIFICATIONS

TC 1MUSBCA White USB-C to USB 3.0A Cable 1m (3.2ft)

SHEATH: PVC, OUTER DIAMETER

4.0 mm (0.16")

CONDUCTOR THICKNESS

22+30 AWG

BANDWIDTH

480Mbit/s

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.03 kg (0.06 lb)

PRODUCT WEIGHT

0.023 kg (0.05 lb)

PACKAGED DIMENSIONS

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

USB 3.0 CABLE

NICKEL-PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

TC 2MUSBCA White USB-C to USB 3.0A Cable 2m (6.5ft)

SHEATH: PVC, OUTER DIAMETER

4.0 mm (0.16")

CONDUCTOR THICKNESS

22+30 AWG

BANDWIDTH

480Mbit/s

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.07 kg (0.15 lb)

PRODUCT WEIGHT

0.063 kg (0.14 lb)

PACKAGED DIMENSIONS

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

USB 3.0 CABLE**NICKEL-PLATED CONNECTORS**

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

TC 3MUSBCA White USB-C to USB 3.0A Cable 3m (9.8ft)

SHEATH: PVC, OUTER DIAMETER

4.0 mm (0.16")

CONDUCTOR THICKNESS

22+30 AWG

BANDWIDTH

5Gbps

CHARGING CURRENT

3 A

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.1 kg (0.22 lb)

PRODUCT WEIGHT

0.090 kg (0.20 lb)

PACKAGED DIMENSIONS

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

USB 3.0 CABLE**NICKEL-PLATED CONNECTORS**

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB