



On one end: HDMI - plugs into a display device.

On the other end: USB type C - the new smaller reversible USB plug which supports USB 3.1 signal.

2m (6.5ft)

TC 2MUSBCHDMI EU SAP: 4322266 US SAP: 12939454

3m (9.8ft) END OF LIFE

TC 3MUSBCHDMI EU SAP: 4322274 US SAP: 12939455

SPECIFICATIONS

TC 2MUSBCHDMI White USB-C to HDMI Cable 2m (6.5ft)

MAXIMUM RESOLUTION

3840 x 2160 (4K) @ 60 Hz

SHEATH: PVC, OUTER DIAMETER

4.7 mm (0.19")

CONDUCTOR THICKNESS

32 AWG

BANDWIDTH

480Mbit/s

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.10 kg (0.22 lb)

PRODUCT WEIGHT

0.088 kg (0.19 lb)

PACKAGED DIMENSIONS

270 mm x 220 mm (10.6" x 8.7")

USB 3.1 CABLE

GOLD PLATED CONNECTORS

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

WORKS WITH IPAD

TC 3MUSBCHDMI White USB-C to HDMI Cable 3m (9.8ft)

MAXIMUM RESOLUTION

3840 x 2160 (4K) @ 60 Hz

SHEATH: PVC, OUTER DIAMETER

4.7 mm (0.19")

CONDUCTOR THICKNESS

32 AWG

BANDWIDTH

480Mbit/s

COMPLIANCE

RoHS, CE, FCC

PACKAGED WEIGHT

0.13 kg (0.29 lb)

PRODUCT WEIGHT

0.118 kg (0.26 lb)

PACKAGED DIMENSIONS

270 mm x 220 mm (10.6" x 8.7")

USB 3.1 CABLE**GOLD PLATED CONNECTORS**

SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB

WORKS WITH IPAD