



Plugs into the VGA socket on your computer - which is often blue - and connects to a display device at the other end.

For VGA cables pre-terminated for Vision's Techconnect Modular Faceplate click here.

**1m (3.2ft)** END OF LIFE

TC 1MVGAP EU SAP: 3546047 US SAP: 12939482

**2m (6.5ft)**

TC 2MVGAP EU SAP: 3265174 US SAP: 12939567

**3m (9.8ft)**

TC 3MVGAP EU SAP: 3265175 US SAP: 12939568

**5m (16.4ft)**

TC 5MVGAP EU SAP: 3265176 US SAP: 12939569

**10m (32.8ft)**

TC 10MVGAP EU SAP: 3480006 US SAP: 12939483

**15m (49.2ft)**

TC 15MVGAP EU SAP: 3480007 US SAP: 12939484

**20m (65.6ft)** END OF LIFE

TC 20MVGAP EU SAP: 3480008 US SAP: 12939485

### SPECIFICATIONS

#### TC 1MVGAP White VGA Cable 1m (3.2ft)

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.12 kg (0.26 lb)

**PACKAGED DIMENSIONS**

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE**

**GOLD-PLATED CONNECTORS**

**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID**

**AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 2MVGAP White VGA Cable 2m (6.5ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.17 kg (0.37 lb)

**PACKAGED DIMENSIONS**

180 x 180 x 70 mm (7.1" x 7.1" x 2.8")

**LENGTH**

2m (6.5ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 3MVGAP White VGA Cable 3m (9.8ft)

---

**COLOUR**

White

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.22 kg (0.49 lb)

**PACKAGED DIMENSIONS**

180 x 180 x 70 mm (7.1" x 7.1" x 2.8")

**LENGTH**

3m (9.8ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 5MVGAP White VGA Cable 5m (16.4ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.50 kg (1.1 lb)

**PACKAGED DIMENSIONS**

180 x 180 x 70 mm (7.1" x 7.1" x 2.8")

**LENGTH**

5m (16.4ft)

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 10MVGAP White VGA Cable 10m (32.8ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Ω/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.91 kg (2.0 lbs)

**PACKAGED DIMENSIONS**

200 x 200 x 90 mm (7.87" x 7.87" x 3.54")

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE BRAIDED SHIELD**

## TC 15MVGAP White VGA Cable 15m (49.2ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

1.51 kg (3.33 lbs)

**PACKAGED DIMENSIONS**

200 x 200 x 90 mm (7.87" x 7.87" x 3.54")

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE  
BRAIDED SHIELD**

## TC 20MVGAP White VGA Cable 20m (65.6ft)

---

**SHEATH: PVC, OUTER DIAMETER**

8.0 mm (0.31")

**CONDUCTOR THICKNESS**

28 AWG

**IMPEDANCE**

at 10MHz, 75Ω (coaxial cable)

**RESISTANCE**

20°C(Q/1000m) 237.25

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

1.71 kg (3.77 lbs)

**PACKAGED DIMENSIONS**

200 x 200 x 90 mm (7.87" x 7.87" x 3.54")

**FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE****GOLD-PLATED CONNECTORS****DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****AL-MG ALLOY WIRE OVERALL, MORE THAN 65% COVERAGE  
BRAIDED SHIELD**