



This simple patch cable connects your phone or laptop to most audio systems. Minijacks are also known as 1/8", or TRS jack (tip-ring-sleeve) and 3.5 mm / 0.14" jack. They carry a "line-level" signal.

Includes female-minijack to phoenix adaptor, to allow connection to rear of Techconnect modules.

### 1m (3.2ft) END OF LIFE

TC 1M3.5MMP EU SAP: 3546048 US SAP: 12939457

### 2m (6.6ft)

TC 2M3.5MMP EU SAP: 3265183 US SAP: 12939557

### 3m (9.8ft)

TC 3M3.5MMP EU SAP: 4500881 US SAP: 13041711

### 5m (16.4ft)

TC 5M3.5MMP EU SAP: 4536894 US SAP: 13041712

### 10m (32.8ft)

TC 10M3.5MMP EU SAP: 4536895 US SAP: 13041713

### 15m (49.2ft) END OF LIFE

TC 15M3.5MMP EU SAP: 4536896 US SAP: 13041714

## SPECIFICATIONS

### TC 1M3.5MMP White Minijack Cable 1m (3.2ft)

#### INSULATION

Double-insulated with Aluminium foil

#### SHEATH

PVC, outer diameter: 3 mm (0.11")

#### CONDUCTOR THICKNESS

26AWG

#### PACKAGED WEIGHT

0.03 kg ( 0.07 lb)

#### PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

#### GOLD-PLATED CONNECTORS

#### NARROW PLUG TO FIT IPHONE SOCKETS

#### TINNED COPPER SPIRAL SHIELDING

### TC 2M3.5MMP White Minijack Cable 2m (6.6ft)

#### INSULATION

Double-insulated with Aluminium foil

#### SHEATH

PVC, outer diameter: 3 mm (0.11")

#### CONDUCTOR THICKNESS

26AWG

#### PACKAGED WEIGHT

0.04 kg ( 0.09 lb)

#### PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

#### GOLD-PLATED CONNECTORS

#### NARROW PLUG TO FIT IPHONE SOCKETS

#### TINNED COPPER SPIRAL SHIELDING

## TC 3M3.5MMP White Minijack Cable 3m (9.8ft)

---

### INSULATION

Double-insulated with Aluminium foil

### SHEATH

PVC, outer diameter: 3 mm (0.11")

### CONDUCTOR THICKNESS

26AWG

### PACKAGED WEIGHT

0.11 kg ( 0.24 lb)

### PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

### GOLD-PLATED CONNECTORS

### NARROW PLUG TO FIT IPHONE SOCKETS

### TINNED COPPER SPIRAL SHIELDING

## TC 5M3.5MMP White Minijack Cable 5m (16.4ft)

---

### INSULATION

Double-insulated with Aluminium foil

### SHEATH

PVC, outer diameter: 3 mm (0.11")

### CONDUCTOR THICKNESS

26AWG

### PACKAGED WEIGHT

0.1 kg ( 0.22 lb)

### PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

### GOLD-PLATED CONNECTORS

### NARROW PLUG TO FIT IPHONE SOCKETS

### TINNED COPPER SPIRAL SHIELDING

## TC 10M3.5MMP White Minijack Cable 10m (32.8ft)

---

### INSULATION

Double-insulated with Aluminium foil

### SHEATH

PVC, outer diameter: 3 mm (0.11")

### CONDUCTOR THICKNESS

26AWG

### PACKAGED WEIGHT

0.2 kg ( 0.44 lb)

### PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

### GOLD-PLATED CONNECTORS

### NARROW PLUG TO FIT IPHONE SOCKETS

### TINNED COPPER SPIRAL SHIELDING

## TC 15M3.5MMP White Minijack Cable 15m (49.2ft)

---

### INSULATION

Double-insulated with Aluminium foil

### SHEATH

PVC, outer diameter: 3 mm (0.11")

### CONDUCTOR THICKNESS

26AWG

### PACKAGED WEIGHT

0.3 kg ( 0.66 lb)

### PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

### GOLD-PLATED CONNECTORS

### NARROW PLUG TO FIT IPHONE SOCKETS

### TINNED COPPER SPIRAL SHIELDING