



Braided HDMI Cable 5m (16.4ft)

TC 5MHDMI/HQ EU SAP: 4911405 US SAP: 13557641

vav.link/tc_5mhdmi-hq

Anti Tangle

A soft-woven low-friction outer sheath slides easily as the cable is pulled and helps reduce tangle.

Aramid

Reinforced with Aramid fibre - the material bullet proof vests are made from - to protect from crush and stretch damage.

IMAGE

Product Images

ZIP 1.29 MB

files.visionaudiovisual.com/products/TC2_5MHDMI/images/TC2_5MHDMI.zip

Product Images

ZIP 1.13 MB

files.visionaudiovisual.com/products/TC_5MHDMI-HQ/images/TC_5MHDMI-HQ.zip

Image 1

PNG 1.15 MB

files.visionaudiovisual.com/products/TC_5MHDMI-HQ/images/TC_5MHDMI-HQ-1.png

SPECIFICATIONS

HDMI VERSION

v2.0 (4K @ 60Hz)

BANDWIDTH

340 MHz

SHEATH OUTER DIAMETER

7.8 mm (0.31")

CONDUCTOR THICKNESS

28 AWG (American Wire Gauge)

PACKAGED WEIGHT

0.49 kg (0.86 lb)

PRODUCT WEIGHT

0.39 kg (1.08 lb)

PACKAGED DIMENSIONS

180 mm x 180 mm x 70 mm (7.1" x 7.1" x 2.8")

COLOUR

Braided

CONNECTORS

GOLD-PLATED

DATA TRANSFER RATE

18 Gbit/s

TYPE OF SHIELDING

Double Shielded

AUDIO RETURN CHANNEL (ARC)

Yes

4K COMPLIANT

HIGH-SPEED (CATEGORY 2) WITH ETHERNET