



Control systems for audio-visual and industrial applications use RS-232 which is a 2-way standard which allows the control system to send commands and receive feedback. RS-232 (and RS-485) uses serial cable which has 9-pin d-sub connectors which look like a VGA connector but instead of three rows of pins they only have two.

2m (6.5ft) **END OF LIFE AUGUST 2021**

TC 2MS EU SAP: 3265213 US SAP: 12939458

5m (16.4ft) **END OF LIFE**

TC 5MS EU SAP: 3265214 US SAP: 12939559

10m (32.8ft) **END OF LIFE**

TC 10MS EU SAP: 3265216 US SAP: 12939560

15m (49.2ft) **END OF LIFE AUGUST 2021**

TC 15MS EU SAP: 3265217 US SAP: 12939561

SPECIFICATIONS

TC 2MS White 9-Pin RS-232 Serial Cable 2m (6.5ft)

SHEATH

PVC, outer diameter: 5 mm (0.20")

CONDUCTOR THICKNESS

28 AWG

SHIELD

> 65% coverage braided shield

IMPEDANCE

at 10 MHz, 75Ω (coaxial cable)

RESISTANCE

20°C(Ω/1000 m) 237.25

PACKAGED WEIGHT

0.09 kg (0.2 lb)

PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

CONFORMITY

CE, FCC, Retail packaging

NICKEL-PLATED CONNECTORS

PINS WIRED STRAIGHT THROUGH (I.E. 1 TO 1, 2 TO 1, ETC)

DRAIN WIRE LAID BETWEEN ALUMINUM BRAID

AL-MG ALLOY WIRE OVERALL

TC 5MS White 9-Pin RS-232 Serial Cable 5m (16.4ft)

SHEATH

PVC, outer diameter: 5 mm (0.20")

CONDUCTOR THICKNESS

28 AWG

SHIELD

> 65% coverage braided shield

IMPEDANCE

at 10 MHz, 75Ω (coaxial cable)

RESISTANCE

20°C(Ω/1000 m) 237.25

PACKAGED WEIGHT

0.23 kg (0.51 lb)

PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

CONFORMITY

CE, FCC, Retail packaging

NICKEL-PLATED CONNECTORS

PINS WIRED STRAIGHT THROUGH (I.E. 1 TO 1, 2 TO 1, ETC)

DRAIN WIRE LAID BETWEEN ALUMINUM BRAID

AL-MG ALLOY WIRE OVERALL

TC 10MS White 9-Pin RS-232 Serial Cable 10m (32.8ft)

SHEATH

PVC, outer diameter: 5 mm (0.20")

CONDUCTOR THICKNESS

28 AWG

SHIELD

> 65% coverage braided shield

IMPEDANCE

at 10 MHz, 75Ω (coaxial cable)

RESISTANCE

20°C(Ω/1000 m) 237.25

PACKAGED WEIGHT

0.45 kg (0.99 lb)

PACKAGED DIMENSION

180 x 180 x 70 mm (7.1" x 7.1" x 2.8")

CONFORMITY

CE, FCC, Retail packaging

NICKEL-PLATED CONNECTORS

PINS WIRED STRAIGHT THROUGH (I.E. 1 TO 1, 2 TO 1, ETC)

DRAIN WIRE LAID BETWEEN ALUMINUM BRAID

AL-MG ALLOY WIRE OVERALL

TC 15MS White 9-Pin RS-232 Serial Cable 15m (49.2ft)

SHEATH

PVC, outer diameter: 5 mm (0.20")

CONDUCTOR THICKNESS

28 AWG

SHIELD

> 65% coverage braided shield

IMPEDANCE

at 10 MHz, 75Ω (coaxial cable)

RESISTANCE

20°C(Ω/1000 m) 237.25

PACKAGED WEIGHT

0.68 kg (1.5 lb)

PACKAGED DIMENSION

180 x 180 x 70 mm (7.1" x 7.1" x 2.8")

CONFORMITY

CE, FCC, Retail packaging

NICKEL-PLATED CONNECTORS

PINS WIRED STRAIGHT THROUGH (I.E. 1 TO 1, 2 TO 1, ETC)

DRAIN WIRE LAID BETWEEN ALUMINUM BRAID

AL-MG ALLOY WIRE OVERALL