

- Portable heavy-duty mobile cart
- Supports two displays up to 80 kg (176 lb) in total
- Centre camera shelf included
- 800 mm (31.5") height adjustment, motorised
- Control by wired controller or RS-232
- Removable wheels for non-portable variation
- Removable rear legs to lean against walls



Need to install a Microsoft Teams or Zoom room? Vision's VFM-F50T Dual trolley makes it easy to install two displays on one floor stand. This kit comprises the portable F50T with a dual-display adaptor rail, and a second wall mount.

The F50T has motorised height adjustment so with a one-button press, you can raise it to so you can raise it high for bigger rooms, or lower it to align with the height of a meeting table.

Components included:

SWL 80 kg (176 lbs)

The F50T utilizes heavy-gauge components to support the weight. The weight of all displays combined cannot exceed this.

Four cartons

This kit contains 1 x VFM-F50T floor stand (comes in two cartons strapped together), 1 x VFM-F50_DL rail accessory, and 1 x VFM-W8X6 wall mount. If you need a different combination you can order each part separately.

Wired Control or RS-232

A wired remote control offers up and down functions. Additionally, you have the option to use an RS-232 control system, which allows you to add pre-set positions, as well as upper and lower limits.

4" Wheels

Medical-grade 4" (100 mm) castors glide over any bumps, making the stand easy to pull even on deep carpet. Big wheels reduce vibration. All wheels are lockable.

Hide Mess

The front cover is removable, facilitating cable routing. And you can conceal source devices or power distribution boards inside the column.

Landscape or Portrait

Vision's VESA mounts support portrait or landscape orientation.

800 mm / 31.5" Motorised Height Adjustment

Motorized height adjustment allows for easy alteration of the display's height to accommodate different audience preferences and needs.

Increased Safety

A safety sensor halts motor when display lowers onto obstacle.

Camera Shelf

Positioning the camera at the centre of the two screens enhances the impression of natural eye contact for remote participants. The F50 stand offers the flexibility to fix a centre shelf above, below, or between the two screens. If using a smaller camera like the Logitech Brio, the platform part of the shelf assembly can be omitted.

2 x Displays

Support two displays from 55" to 86". Each display can weight up to 40 kg. The aluminium rail comes in three parts and allows side to side adjustment of the displays.

Non-Portable / Free-Standing

Sometimes users need a non-portable free-standing solution, so simply remove the wheels and fit the adjustable feet. The feet are low profile to reduce trip hazards.

Glass Walls

Do you have a meeting room with a non-structural or glass wall? The F50T feet can be configured to safely support the stand leaning against glass. Changing the rear leg angle allows positioning the display against the wall without any load on it.

SPECIFICATIONS

VFM-F50T/D Motorised Dual Flat Panel Floor Stand

PRODUCT DIMENSIONS

See CAD

SAFE WORKING LOAD

80 kg / 176 lbs (40 kg / 88 lbs per display)

CONSTRUCTION MATERIAL

Steel, Aluminium

COLOUR

Powercoated Matt Black

VESA SIZES

800 x 600 mm 800 x 500 mm 800 x 400 mm 600 x 600 mm 600 x 500 mm 600 x 400 mm 500 x 500 mm 500 x 400 mm 400 x 600 mm 400 x 400 mm 400 x 300 mm 400 x 200 mm 300 x 400 mm 300 x 300 mm

MOTOR TYPE

Linear-drive

MOVEMENT SPEED

16 mm / 0.6" per second

HEIGHT ADJUSTMENT RANGE

800 mm / 31.5"

ACCESSORIES INCLUDED

1 x EU Figure-8 C7 Power cable 2.5 m (8 ft) long 1 x UK Figure-8 C7 Power cable 2.5 m (8 ft) long 1 x AU Figure-8 C7 Power cable 2.5 m (8 ft) long 1 x Remote Control with cable 1.5 m (5 ft) long 2 x Wall Brackets 8 x M5 16 mm screw 8 x M6 16 mm screw 8 x M6 25 mm screw 8 x M8 30 mm screw 8 x M8 50 mm screw 8 x 15 mm thick nylon spacers (for 2S 85" Microsoft Surface Hub) 8 x 20 mm thick nylon spacers (for 2S 85" Microsoft Surface Hub) 1 x Camera Shelf 2 x Extrusion end covers 12 x T-Slot M6 Bolts with T-Slot nuts

POWER SUPPLY

110-230V Integrated Power Supply

WARRANTY

Lifetime return-to-base UK Only: 5 years onsite, 1 engineer provided so requires assistance

COMPLIANCES

RoHS, WEEE, FCC, CE/EMC, CE/LVD, RCM/DOC, RCM/POC Certification not held but complies with ISO 22881:2004 BS EN 12527:1999 BS EN 12531:1999

