VISION

VFM-VW6X4 Video Wall Mount 600×400

<u>vav.link/vfm-vw6x4</u> VFM-VW6X4 EU SAP: 4758641 US SAP: 13445511 END OF LIFE AUGUST 2022



Wall Mount for displays with mounting points up to 600 x 400mm apart Pop-out style for fast access and adjustment Fine tilt, rotation, depth, and height adjustment Displays 45-86"



Aligning displays on a video wall is painstaking, so every detail has been thought about on this mount to ensure it is as fast as possible to install, and as easy as possible to adjust with precision.

Landscape or Portrait

This mount supports displays in either portrait or landscape. In portrait format the display must be more than 650 mm (26") wide and must be VESA $400 \times 400 = 100$ mm or less.

Minimal Tools

Wherever possible Vision uses thumbscrews which dramatically speed up installation and help with faster adjustment.

Display Fixing Screws

Vision include more screw sizes than other manufacturers to ensure you get that display on the wall as quickly as possible every time.

Pop-out

A light push on the display releases the scissor pop-out mechanism, pushing the display out towards you. Plastic tongues are included which are put into place once you are done to avoid accidental pop-outs.

Quick-Release

Fix the vertical arms to the rear of the display, then lower this assembly onto the wall bracket. It will latch into place. It can be removed by pushing a quick release lever.

Tilt

Adjust tilt by -2 to 4° with screws positioned at the top of the vertical display arms.

Rotation and Height

Adjust rotation by -3 to 3° with screws, also positioned at the top of the display arms.

Depth adjustment

The depth of each side can be adjusted independently with a hex key on the side of the vertical display arms.

45-86" displays

Fits any flat-panel LCD or LED screen which has rear mounting holes up to 600 wide x 400mm tall apart.

Depth

The minimum depth in place is 95 mm (3.7"), and when it pops out it comes 285 mm (11.2").

Lockable

It latches into place and can be locked with a padlock (not included) for further security.

PRODUCT DIMENSIONS

 $670 \times 524 \times 95\text{-}285 \text{ mm} / 26.4" \times 20.6" \times 3.7\text{-}11.2" (height x width x depth)$

PACKAGED DIMENSIONS

740 x 271 x 138 mm / 29.13" x 10.67" x 5.43"

PRODUCT WEIGHT

10.45 kg (23.04 lbs)

PACKAGED WEIGHT

11.50 kg (25.35 lbs)

SAFE WORKING LOAD

70 kg (154 lbs)

CONTRUCTION MATERIAL

Steel (3.0 mm hot rolled plate; 2.5 mm hot rolled plate; 2.0 mm cold rolled plate)

COLOUR

Black

VESA SIZES

 600×400 mm 500×400 mm 400×400 mm 400×300 mm 400×200 mm 300×400 mm 300×300 mm 200×400 mm 200×200 mm

ACCESSORIES INCLUDED

 $4 \times M5 14 \text{ mm } (0.55") \text{ screw } 4 \times M5 25 \text{ mm } (1") \text{ screw } 4 \times M6 14 \text{ mm } (0.55") \text{ screw } 4 \times M6 30 \text{ mm } (1.2") \text{ screw } 4 \times M8 20 \text{ mm } (1") \text{ screw } 4 \times M8 30 \text{ mm } (1.2") \text{ sc$

WARRANTY

Lifetime return-to-base

COMPLIANCES

RoHS, REACH, UL

