

VFM-W4X4TV/2 Tilting Flat-Panel Wall Mount 400×400

vav.link/vfm-w4x4tv-2 VFM-W4X4TV/2 EU SAP: 6333311



Tilting Wall Mount for large-format flat panels 32-65" (subject to VESA pattern and weight limit)
Mounting points up to 400 (wide) x 400 mm (tall) apart
Light Duty 60 kg / 132 lb SWL
Lockable



Vision's VFM-W4X4TV/2 wall-mount for large-format flatpanels is designed for price-sensitive installations where no fancy features are required. To hit the right price point and ease of installation, we've simplified the design and engineered down the cost by reducing the amount of materials used, but without compromise on robustness and reliability.

It fits any flat-panel LCD or LED screen from 32- to 65-inch with rear mounting holes up to 400x400mm apart with a maximum weight 60kg. Everything an installer needs to put the display on the wall is included in the box.

Flexible installation

The VFM-W4X4TV/2 mount is fast to fix, thanks to a proven design with slotted holes on the horizontal part to allow easy fix to stud wall and side-to-side adjustment.

Everything included for installation

Vision puts everything the installer needs in the VFM-W4X4TV/2 pack, including a load of M5, 6 and 8 bolts in varying lengths to fix the vertical arms to the rear of the display.

Safe Working Load of 60kg

The VFM-W4X4TV/2 mount supports flat-panel displays weighing up to 60kg (132 lbs).

Fits Displays of 32-to 65-inch

Fits most displays sized from 32- to 65-inch, subject to VESA pattern and weight. Curved screens are not supported by this mount.

Meets ADA Regulations

The slim design holds the display just 49 mm (1.9-inch) off the wall, which not only looks better, reduces snagging and enables a higher safe working load rating, as well as meeting ADA regulations.

Folding Frame

The part that fixes to the wall comes pre-assembled to reduce fiddly assembly. It unfolds in seconds to deploy.

Latches in Place

Once in place locking strips slide up to prevent the assembly being lifted off the bracket by opportunistic thieves. Quick-release cords pull down to unlatch.

15° Tilt

The tilting mechanism tilts up 3° or down 12°. The effortless adjustment makes it easy to set the best viewing angle.

Open Architecture

The open centre of the wall plate allows cables to be fed into the wall easily, all completely hidden behind the display.

Lockable

Holes are in place to secure the display with a padlock (not included).

SPECIFICATIONS

PRODUCT DIMENSIONS

 $445 \times 431 \times 49 \text{ mm} / 17.5" \times 17.0" \times 1.9" \text{ (width x height x depth)}$

PACKAGED DIMENSIONS

450 x 122 x 64 mm / 17.7" x 4.8" x 3.4"

PRODUCT WEIGHT

1.86 kg (4.1 lbs)

PACKAGED WEIGHT

1.9 kg (4.2 lbs)

SAFE WORKING LOAD

60 kg (132 lbs)

CONTRUCTION MATERIAL

Cold-rolled Steel 2 mm (0.08")

COLOUR

Powdercoated Black

VESA SIZES

 $400 \times 400 \text{ mm} \ 400 \times 300 \text{ mm} \ 400 \times 200 \text{ mm} \ 300 \times 400 \text{ mm} \ 300 \times 300 \text{ mm} \ 200 \times 400 \text{ mm} \ 200 \times 300 \text{ mm} \ 200 \times 200 \text{ mm} \ 150 \times 200 \text{ mm}$

ACCESSORIES INCLUDED

4 x M5 14 mm screw 4 x M6 14 mm screw 4 x M6 30 mm screw 4 x M8 30 mm screw 4 x M8 50 mm screw

WARRANTY

Lifetime return-to-base

COMPLIANCES

RoHS, ADA (Americans with Disability Act) Compliant