

Tilting Wall Mount for large-format flat panels 47-90"  
 (subject to VESA pattern and weight limit)  
 Mounting points up to 800 (wide) x 600 mm (tall) apart  
 Heavy duty 90 kg / 198 lb SWL  
 Display latches in place  
 Optional camera shelf



Vision's engineering team has designed this mount with professional AV installers in mind. It offers uncompromising strength, quick installation, and high adjustability, with all necessary components included. The VFM-W8X6S is compatible with any flat-panel LCD or LED screen that has rear mounting holes up to 800 mm wide by 600 mm tall.

Additionally, it features an innovative slide-out stowage system for concealing power distribution boards and mini PCs behind the display.

### Heavy Duty

Interactive flat panels are large and very heavy. Vision's VFM-W8X6S uses heavy gauge sheet metal to take the weight up to SWL 90 kg / 198 lb safely.

### Everything Included

Vision includes everything you need including a load of M5, 6, and 8 bolts in varying lengths to fix the vertical arms to the rear of the display.

### For 47-90" Displays

Fits most displays from 47-90" subject to VESA pattern and weight limit. Note: curved screens are not supported by this mount.

### Designed for Professionals

A proven design allows fast fixing, and slotted holes on the wall part allowing levelling adjustment after fixing.

### Latches Securely

The display latches on the horizontal section as the display is hung in place. Snap the plastic pull-rods off to length so they are hidden behind the display. Give the pull-rods a downward tug to unlatch the display.

### Video Conference Shelf

An optional shelf fixes in the centre above or below the display. Any camera including the Logitech Rally or Meetup can be fixed to the shelf. *Part Number: VFM-WVC/2 [SAP: 8271288]*

### Tilt

Ideal in applications where the display is mounted high, this mount features tilt to direct the display downward.

### Slide-Out Storage

Fix media players, mini-PCs, and power distribution boards on the slide-out section, simplifying maintenance access.

## SPECIFICATIONS

**PRODUCT DIMENSIONS**

845 x 635 x 51 mm / 33.3" x 25.0" x 2.0" (width x height x depth)

**PACKAGED DIMENSIONS**

880 x 235 x 55 mm / 34.6" x 9.3" x 2.2"

**PRODUCT WEIGHT**

6.2 kg (13.6 lbs)

**PACKAGED WEIGHT**

7.5 kg (16.5 lbs)

**SAFE WORKING LOAD**

130 kg / 287 lb

**CONSTRUCTION MATERIAL**

Cold-rolled Steel 3 mm (0.12")

**COLOUR**

Black

**VESA SIZES**

800 x 600 mm 800 x 500 mm 800 x 400 mm 700 x 400 mm 600 x 600 mm 600 x 500 mm 600 x 400 mm 500 x 500 mm 500 x 400 mm 400 x 600 mm 400 x 400 mm 400 x 300 mm 400 x 200 mm 300 x 400 mm 300 x 300 mm

**ACCESSORIES INCLUDED**

4 x M5 16 mm screw 4 x M6 16 mm screw 4 x M6 25 mm screw 4 x M8 30 mm screw 4 x M8 50 mm screw 4 x 13 mm thick nylon spacers 4 x 20 mm thick nylon spacers

**WARRANTY**

Lifetime return-to-base

**COMPLIANCES**

RoHS, ADA (Americans with Disability Act) Compliant